

# Package ‘metacor’

September 26, 2025

**Type** Package

**Title** Meta-Analytic Effect Size Calculation for Pre-Post Designs with Correlation Imputation

**Version** 1.2.0

**Description** Tools for the calculation of effect sizes (standardised mean difference) and mean difference in pre-post controlled studies, including robust imputation of missing variances (standard deviation of changes) and correlations (Pearson correlation coefficient). The main function 'metacor\_dual()' implements several methods for imputing missing standard deviation of changes or Pearson correlation coefficient, and generates transparent imputation reports. Designed for meta-analyses with incomplete summary statistics. For details on the methods, see Higgins et al. (2023) and Fu et al. (2013).

**License** MIT + file LICENSE

**URL** <https://github.com/ikerugr/metacor>,  
<https://ikerugr.r-universe.dev/metacor>

**BugReports** <https://github.com/ikerugr/metacor/issues>

**Depends** R (>= 3.6)

**Imports** stats, officer, stringr

**Suggests** knitr, rmarkdown, testthat (>= 3.0.0)

**Config/testthat/edition** 3

**Encoding** UTF-8

**RoxygenNote** 7.3.2

**VignetteBuilder** knitr

**NeedsCompilation** no

**Author** Iker J. Bautista [aut, cre],  
Saul M. Rodriguez [ctb]

**Maintainer** Iker J. Bautista <ikerugr@gmail.com>

**Repository** CRAN

**Date/Publication** 2025-09-26 07:00:03 UTC

## Contents

|                        |   |
|------------------------|---|
| metacor_dual . . . . . | 2 |
|------------------------|---|

|              |          |
|--------------|----------|
| <b>Index</b> | <b>4</b> |
|--------------|----------|

---

|              |                                                                                                                                              |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| metacor_dual | <i>Effect Sizes and Imputation for Meta-Analysis of Pre-Post Studies and Pre-Post intervention and control groups studies (metacor_dual)</i> |
|--------------|----------------------------------------------------------------------------------------------------------------------------------------------|

---

### Description

Calculates effect sizes (i.e., SMDpre, SMDchange, ScMDpooled, ScMDpre) and allows for various imputation methods (i.e., none, cv, direct, mean) for missing SDdiff and correlation coefficients in pre-post meta-analyses, with or without a control group. Generates a detailed imputation report in Word format.

### Usage

```
metacor_dual(
  df,
  digits = NULL,
  add_to_df = TRUE,
  method = "both",
  apply_hedges = TRUE,
  SMD_method = "SMDpre",
  MeanDifferences = FALSE,
  impute_method = "none",
  verbose = TRUE,
  report_imputations = FALSE,
  custom_sd_diff_int = NULL,
  custom_sd_diff_con = NULL,
  single_group = FALSE
)
```

### Arguments

|                 |                                                                                         |
|-----------------|-----------------------------------------------------------------------------------------|
| df              | Data frame with the necessary columns for intervention and (optionally) control groups. |
| digits          | Number of decimal places to round results (default: NULL).                              |
| add_to_df       | Logical. If TRUE, results are added to the original data frame.                         |
| method          | Method for SDdiff calculation (i.e., 'p_value', 'ci', 'both').                          |
| apply_hedges    | Logical. Apply Hedges' g correction? (default: TRUE)                                    |
| SMD_method      | Method for effect size (i.e., 'SMDpre', 'SMDchange', 'ScMDpooled', 'ScMDpre').          |
| MeanDifferences | Logical. Calculate mean differences and variances? (default: FALSE)                     |

```

impute_method  Imputation method for missing SDdiff (i.e., 'none', 'direct', 'mean', 'cv').
verbose        Logical. Print messages during processing? (default: TRUE)
report_imputations
                Logical. Generate Word imputation report? (default: FALSE)
custom_sd_diff_int
                List with elements 'row' and 'value' for manual sd_diff_int values.
custom_sd_diff_con
                List with elements 'row' and 'value' for manual sd_diff_con values.
single_group   Logical. Is the design single-group only? (default: FALSE)

```

### Value

Data frame with calculated variables. Optionally, a Word report ('imputation\_report.docx') is generated.

### References

Higgins, J. P. T., Thomas, J., Chandler, J., Cumpston, M., Li, T., Page, M. J., & Welch, V. A. (Eds.). (2023). Cochrane handbook for systematic reviews of interventions (Version 6.3). Cochrane. <https://training.cochrane.org/handbook> Fu, R., Vandermeer, B.W., Shamliyan, T.A., O'Neil, M.E., Yazdi, F., Fox, S.H., & Morton, S.C. (2013). Handling Continuous Outcomes in Quantitative Synthesis. Methods Guide for Comparative Effectiveness Reviews. AHRQ Publication No. 13-EHC103-EF. <https://effectivehealthcare.ahrq.gov/reports/final.cfm>

### Examples

```

df <- data.frame(
  study_name = c("Study1", "Study2", "Study3", "Study4",
    "Study5", "Study6", "Study7", "Study8", "Study9"),
  p_value_Int = c(1.038814e-07, NA, NA, NA, NA, 2.100000e-02, NA, NA, NA),
  n_Int = c(10, 10, 10, 10, 15, 15, 10, 10, 10),
  meanPre_Int = c(8.17, 10.09, 10.18, 9.85, 9.51, 7.70, 10.00, 11.53, 11.20),
  meanPost_Int = c(10.12, 12.50, 12.56, 10.41, 10.88, 9.20, 10.80, 13.42, 12.00),
  sd_pre_Int = c(1.83, 0.67, 0.66, 0.90, 0.62, 0.90, 0.70, 0.60, 1.90),
  sd_post_Int = c(1.85, 0.72, 0.97, 0.67, 0.76, 1.10, 0.70, 0.80, 1.80),
  upperCI_Int = c(NA, NA, NA, NA, NA, NA, NA, NA, NA),
  lowerCI_Int = c(NA, NA, NA, NA, NA, NA, NA, NA, NA)
)
result <- metacor_dual(df)
print(result)

```

# Index

metacor\_dual, [2](#)