

Package ‘olle’

September 6, 2024

Title Policy Learning

Version 1.5

Description Package for evaluating user-specified finite stage policies and learning optimal treatment policies via doubly robust loss functions. Policy learning methods include doubly robust learning of the blip/conditional average treatment effect and sequential policy tree learning. The package also include methods for optimal subgroup analysis. See Nordland and Holst (2022) <[doi:10.48550/arXiv.2212.02335](https://doi.org/10.48550/arXiv.2212.02335)> for documentation and references.

License Apache License (>= 2)

Encoding UTF-8

Depends R (>= 4.0), SuperLearner

Imports data.table (>= 1.14.5), lava (>= 1.7.0), future.apply, progressr, methods, policytree (>= 1.2.0), survival, targeted (>= 0.4), DynTxRegime

Suggests DTRlearn2, glmnet (>= 4.1-6), mgcv, xgboost, knitr, ranger, rmarkdown, testthat (>= 3.0), ggplot2

RoxygenNote 7.3.2

BugReports <https://github.com/AndreasNordland/polle/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Andreas Nordland [aut, cre], Klaus Holst [aut] (<<https://orcid.org/0000-0002-1364-6789>>)

Maintainer Andreas Nordland <andreasnordland@gmail.com>

Repository CRAN

Date/Publication 2024-09-06 14:30:13 UTC

Contents

conditional	3
control_blip	4
control_drql	4

control_earl	5
control_owl	6
control_ptl	7
control_rwl	8
copy_policy_data	9
fit_g_functions	10
get_actions	11
get_action_set	11
get_g_functions	12
get_history_names	13
get_id	14
get_id_stage	15
get_K	16
get_n	16
get_policy	17
get_policy_actions	18
get_policy_functions.blip	19
get_policy_object	21
get_q_functions	22
get_stage_action_sets	23
get_utility	24
g_model	25
history	28
nuisance_functions	30
partial	31
plot.policy_data	32
plot.policy_eval	33
policy	34
policy_data	35
policy_def	38
policy_eval	40
policy_learn	47
predict.nuisance_functions	51
q_model	52
sim_multi_stage	55
sim_single_stage	56
sim_single_stage_multi_actions	58
sim_two_stage	58
sim_two_stage_multi_actions	59
subset_id	60

conditional*Conditional Policy Evaluation*

Description

`conditional()` is used to calculate the policy value for each group defined by a given baseline variable.

Usage

```
conditional(object, policy_data, baseline)
```

Arguments

- | | |
|-------------|---|
| object | Policy evaluation object created by policy_eval() . |
| policy_data | Policy data object created by policy_data() . |
| baseline | Character string. |

Value

object of inherited class 'estimate', see [lava::estimate.default](#). The object is a list with elements 'coef' (policy value estimate for each group) and 'IC' (influence curve estimate matrix).

Examples

```
library("polle")
library("data.table")
setDTthreads(1)
d <- sim_single_stage(n=2e3)
pd <- policy_data(d,
                   action = "A",
                   baseline = c("B"),
                   covariates = c("Z", "L"),
                   utility = "U")

# static policy:
p <- policy_def(1)

pe <- policy_eval(pd,
                  policy = p)

# conditional value for each group defined by B
conditional(pe, pd, "B")
```

<code>control_blip</code>	<i>Control arguments for doubly robust blip-learning</i>
---------------------------	--

Description

`control_blip` sets the default control arguments for doubly robust blip-learning, `type = "blip"`.

Usage

```
control_blip(blip_models = q_glm(~.))
```

Arguments

`blip_models` Single element or list of V-restricted blip-models created by [q_glm\(\)](#), [q_rf\(\)](#), [q_s1\(\)](#) or similar functions.

Value

list of (default) control arguments.

<code>control_drql</code>	<i>Control arguments for doubly robust Q-learning</i>
---------------------------	---

Description

`control_drql` sets the default control arguments for doubly robust Q-learning, `type = "drql"`.

Usage

```
control_drql(qv_models = q_glm(~.))
```

Arguments

`qv_models` Single element or list of V-restricted Q-models created by [q_glm\(\)](#), [q_rf\(\)](#), [q_s1\(\)](#) or similar functions.

Value

list of (default) control arguments.

control_earl

Control arguments for Efficient Augmentation and Relaxation Learning

Description

`control_earl` sets the default control arguments for efficient augmentation and relaxation learning , type = "earl". The arguments are passed directly to [DynTxRegime::earl\(\)](#) if not specified otherwise.

Usage

```
control_earl(
  moPropen,
  moMain,
  moCont,
  regime,
  iter = 0L,
  fSet = NULL,
  lambdas = 0.5,
  cvFolds = 0L,
  surrogate = "hinge",
  kernel = "linear",
  kparam = NULL,
  verbose = 0L
)
```

Arguments

moPropen	Propensity model of class "ModelObj", see modelObj::modelObj .
moMain	Main effects outcome model of class "ModelObj".
moCont	Contrast outcome model of class "ModelObj".
regime	An object of class formula specifying the design of the policy/regime.
iter	Maximum number of iterations for outcome regression.
fSet	A function or NULL defining subset structure.
lambdas	Numeric or numeric vector. Penalty parameter.
cvFolds	Integer. Number of folds for cross-validation of the parameters.
surrogate	The surrogate 0-1 loss function. The options are "logit", "exp", "hinge", "sqhinge", "huber".
kernel	The options are "linear", "poly", "radial".
kparam	Numeric. Kernel parameter
verbose	Integer.

Value

list of (default) control arguments.

`control_owl`

Control arguments for Outcome Weighted Learning

Description

`control_owl()` sets the default control arguments for backwards outcome weighted learning, type = "owl". The arguments are passed directly to [DTRlearn2::owl\(\)](#) if not specified otherwise.

Usage

```
control_owl(
  policy_vars = NULL,
  reuse_scales = TRUE,
  res.lasso = TRUE,
  loss = "hinge",
  kernel = "linear",
  augment = FALSE,
  c = 2^(-2:2),
  sigma = c(0.03, 0.05, 0.07),
  s = 2^(-2:2),
  m = 4
)
```

Arguments

<code>policy_vars</code>	Character vector/string or list of character vectors/strings. Variable names used to restrict the policy. The names must be a subset of the history names, see <code>get_history_names()</code> . Not passed to <code>owl()</code> .
<code>reuse_scales</code>	The history matrix passed to <code>owl()</code> is scaled using <code>scale()</code> as advised. If TRUE, the scales of the history matrix will be saved and reused when applied to (new) test data.
<code>res.lasso</code>	If TRUE a lasso penalty is applied.
<code>loss</code>	Loss function. The options are "hinge", "ramp", "logit", "logit.lasso", "l2", "l2.lasso".
<code>kernel</code>	Type of kernel used by the support vector machine. The options are "linear", "rbf".
<code>augment</code>	If TRUE the outcomes are augmented.
<code>c</code>	Regularization parameter.
<code>sigma</code>	Tuning parameter.
<code>s</code>	Slope parameter.
<code>m</code>	Number of folds for cross-validation of the parameters.

Value

list of (default) control arguments.

control_ptl*Control arguments for Policy Tree Learning*

Description

`control_ptl` sets the default control arguments for doubly robust policy tree learning, type = "ptl". The arguments are passed directly to `policytree::policy_tree()` (or `policytree::hybrid_policy_tree()`) if not specified otherwise.

Usage

```
control_ptl(  
  policy_vars = NULL,  
  hybrid = FALSE,  
  depth = 2,  
  search.depth = 2,  
  split.step = 1,  
  min.node.size = 1  
)
```

Arguments

<code>policy_vars</code>	Character vector/string or list of character vectors/strings. Variable names used to construct the V-restricted policy tree. The names must be a subset of the history names, see <code>get_history_names()</code> . Not passed to <code>policy_tree()</code> .
<code>hybrid</code>	If TRUE, <code>policytree::hybrid_policy_tree()</code> is used to fit a policy tree. Not passed to <code>policy_tree()</code> .
<code>depth</code>	Integer or integer vector. The depth of the fitted policy tree for each stage.
<code>search.depth</code>	(only used if <code>hybrid</code> = TRUE) Integer or integer vector. Depth to look ahead when splitting at each stage.
<code>split.step</code>	Integer or integer vector. The number of possible splits to consider when performing policy tree search at each stage.
<code>min.node.size</code>	Integer or integer vector. The smallest terminal node size permitted at each stage.

Value

list of (default) control arguments.

control_rwl*Control arguments for Residual Weighted Learning*

Description

`control_rwl` sets the default control arguments for residual learning , type = "rwl". The arguments are passed directly to [DynTxRegime::rwl\(\)](#) if not specified otherwise.

Usage

```
control_rwl(
  moPropen,
  moMain,
  regime,
  fSet = NULL,
  lambdas = 2,
  cvFolds = 0L,
  kernel = "linear",
  kparam = NULL,
  responseType = "continuous",
  verbose = 2L
)
```

Arguments

<code>moPropen</code>	Propensity model of class "ModelObj", see modelObj::modelObj .
<code>moMain</code>	Main effects outcome model of class "ModelObj".
<code>regime</code>	An object of class formula specifying the design of the policy/regime.
<code>fSet</code>	A function or NULL defining subset structure.
<code>lambdas</code>	Numeric or numeric vector. Penalty parameter.
<code>cvFolds</code>	Integer. Number of folds for cross-validation of the parameters. "logit", "exp", "hinge", "sqhinge", "huber".
<code>kernel</code>	The options are "linear", "poly", "radial".
<code>kparam</code>	Numeric. Kernel parameter
<code>responseType</code>	Character string. Options are "continuous", "binary", "count".
<code>verbose</code>	Integer.

Value

list of (default) control arguments.

copy_policy_data *Copy Policy Data Object*

Description

Objects of class `policy_data` contains elements of class `data.table::data.table`. `data.table` provide functions that operate on objects by reference. Thus, the `policy_data` object is not copied when modified by reference, see examples. An explicit copy can be made by `copy_policy_data`. The function is a wrapper of `data.table::copy()`.

Usage

```
copy_policy_data(object)
```

Arguments

object Object of class `policy_data`.

Value

Object of class `policy_data`.

Examples

```
library("polle")
### Single stage case: Wide data
d1 <- sim_single_stage(5e2, seed=1)
head(d1, 5)
# constructing policy_data object:
pd1 <- policy_data(d1,
                    action="A",
                    covariates=c("Z", "B", "L"),
                    utility="U")
pd1

# True copy
pd2 <- copy_policy_data(pd1)
# manipulating the data.table by reference:
pd2$baseline_data[, id := id + 1]
head(pd2$baseline_data$id - pd1$baseline_data$id)

# False copy
pd2 <- pd1
# manipulating the data.table by reference:
pd2$baseline_data[, id := id + 1]
head(pd2$baseline_data$id - pd1$baseline_data$id)
```

fit_g_functions *Fit g-functions*

Fit g-functions

Description

`fit_g_functions` is used to fit a list of g-models.

Usage

```
fit_g_functions(policy_data, g_models, full_history = FALSE)
```

Arguments

- | | |
|---------------------------|---|
| <code>policy_data</code> | Policy data object created by policy_data() . |
| <code>g_models</code> | List of action probability models/g-models for each stage created by g_emir() , g_glm() , g_rf() , g_s1() or similar functions. |
| <code>full_history</code> | If TRUE, the full history is used to fit each g-model. If FALSE, the single stage/"Markov type" history is used to fit each g-model. |

Examples

<code>get_actions</code>	<i>Get Actions</i>
--------------------------	--------------------

Description

`get_actions` returns the actions at every stage for every observation in the policy data object.

Usage

```
get_actions(object)
```

Arguments

<code>object</code>	Object of class policy_data .
---------------------	---

Value

[data.table::data.table](#) with keys id and stage and character variable A.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("B"),
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

# getting the actions:
head(get_actions(pd))
```

<code>get_action_set</code>	<i>Get Action Set</i>
-----------------------------	-----------------------

Description

`get_action_set` returns the action set, i.e., the possible actions at each stage for the policy data object.

Usage

```
get_action_set(object)
```

Arguments

object Object of class [policy_data](#).

Value

Character vector.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("B"),
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

# getting the actions set:
get_action_set(pd)
```

get_g_functions *Get g-functions*

Description

`get_g_functions()` returns a list of (fitted) g-functions associated with each stage.

Usage

```
get_g_functions(object)
```

Arguments

object Object of class [policy_eval](#) or [policy_object](#).

Value

List of class [nuisance_functions](#).

See Also

[predict.nuisance_functions](#)

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
                  action = c("A_1", "A_2"),
                  baseline = c("B"),
                  covariates = list(L = c("L_1", "L_2"),
                                     C = c("C_1", "C_2")),
                  utility = c("U_1", "U_2", "U_3"))
pd

# evaluating the static policy a=1 using inverse propensity weighting
# based on a GLM model at each stage
pe <- policy_eval(type = "ipw",
                    policy_data = pd,
                    policy = policy_def(1, reuse = TRUE, name = "A=1"),
                    g_models = list(g_glm(), g_glm()))
pe

# getting the g-functions
g_functions <- get_g_functions(pe)
g_functions

# getting the fitted g-function values
head(predict(g_functions, pd))
```

`get_history_names` *Get history variable names*

Description

`get_history_names()` returns the state covariate names of the history data table for a given stage. The function is useful when specifying the design matrix for `g_model` and `q_model` objects.

Usage

```
get_history_names(object, stage)
```

Arguments

- | | |
|---------------------|---|
| <code>object</code> | Policy data object created by <code>policy_data()</code> . |
| <code>stage</code> | Stage number. If NULL, the state/Markov-type history variable names are returned. |

Value

Character vector.

Examples

```

library("polle")
### Multiple stages:
d3 <- sim_multi_stage(5e2, seed = 1)
pd3 <- policy_data(data = d3$stage_data,
                     baseline_data = d3$baseline_data,
                     type = "long",
                     id = "id",
                     stage = "stage",
                     event = "event",
                     action = "A",
                     utility = "U")
pd3
# state/Markov type history variable names (H):
get_history_names(pd3)
# full history variable names (H_k) at stage 2:
get_history_names(pd3, stage = 2)

```

`get_id` *Get IDs*

Description

`get_id` returns the ID for every observation in the policy data object.

Usage

get_id(object)

Arguments

object Object of class [policy_data](#) or [history](#).

Value

Character vector.

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                  action = c("A_1", "A_2"),
                  baseline = c("B"),
                  covariates = list(L = c("L_1", "L_2"),
                                    C = c("C_1", "C_2")),
                  utility = c("U_1", "U_2", "U_3"))

```

```
# getting the IDs:  
head(get_id(pd))
```

get_id_stage*Get IDs and Stages*

Description

get_id returns the stages for every ID for every observation in the policy data object.

Usage

```
get_id_stage(object)
```

Arguments

object Object of class [policy_data](#) or [history](#).

Value

[data.table::data.table](#) with keys id and stage.

Examples

```
### Two stages:  
d <- sim_two_stage(5e2, seed=1)  
# constructing policy_data object:  
pd <- policy_data(d,  
                 action = c("A_1", "A_2"),  
                 baseline = c("B"),  
                 covariates = list(L = c("L_1", "L_2"),  
                                 C = c("C_1", "C_2")),  
                 utility = c("U_1", "U_2", "U_3"))  
pd  
  
# getting the IDs and stages:  
head(get_id_stage(pd))
```

get_K

*Get Maximal Stages***Description**

`get_K` returns the maximal number of stages for the observations in the policy data object.

Usage

```
get_K(object)
```

Arguments

object	Object of class policy_data .
--------	---

Value

Integer.

Examples

```
d <- sim_multi_stage(5e2, seed = 1)
pd <- policy_data(data = d$stage_data,
                   baseline_data = d$baseline_data,
                   type = "long",
                   id = "id",
                   stage = "stage",
                   event = "event",
                   action = "A",
                   utility = "U")
get_K(pd)
```

get_n

*Get Number of Observations***Description**

`get_n` returns the number of observations in the policy data object.

Usage

```
get_n(object)
```

Arguments

object	Object of class policy_data .
--------	---

Value

Integer.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("B"),
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

# getting the number of observations:
get_n(pd)
```

get_policy

*Get Policy***Description**

`get_policy` extracts the policy from a policy object or a policy evaluation object. The policy is a function which takes a policy data object as input and returns the policy actions.

Usage

```
get_policy(object, threshold = NULL)
```

Arguments

- | | |
|------------------------|--|
| <code>object</code> | Object of class policy_object or policy_eval . |
| <code>threshold</code> | Numeric vector. Thresholds for the first stage policy function. |

Value

function of class [policy](#).

Examples

```
library("polle")
### Two stages:
d <- sim_two_stage(5e2, seed = 1)
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("BB"),
                   covariates = list(
```

```

L = c("L_1", "L_2"),
C = c("C_1", "C_2")
),
utility = c("U_1", "U_2", "U_3")
)
pd

### V-restricted (Doubly Robust) Q-learning

# specifying the learner:
pl <- policy_learn(
  type = "drql",
  control = control_drql(qv_models = q_glm(formula = ~C))
)

# fitting the policy (object):
po <- pl(
  policy_data = pd,
  q_models = q_glm(),
  g_models = g_glm()
)

# getting and applying the policy:
head(get_policy(po)(pd))

# the policy learner can also be evaluated directly:
pe <- policy_eval(
  policy_data = pd,
  policy_learn = pl,
  q_models = q_glm(),
  g_models = g_glm()
)

# getting and applying the policy again:
head(get_policy(pe)(pd))

```

get_policy_actions *Get Policy Actions*

Description

`get_policy_actions()` extract the actions dictated by the (learned and possibly cross-fitted) policy at every stage.

Usage

`get_policy_actions(object)`

Arguments

<code>object</code>	Object of class policy_eval .
---------------------	---

Value

`data.table::data.table` with keys id and stage and action variable d.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

# defining a policy learner based on cross-fitted doubly robust Q-learning:
pl <- policy_learn(type = "drql",
                     control = control_drql(qv_models = list(q_glm(~C_1), q_glm(~C_1+C_2))),
                     full_history = TRUE,
                     L = 2) # number of folds for cross-fitting

# evaluating the policy learner using 2-fold cross fitting:
pe <- policy_eval(type = "dr",
                    policy_data = pd,
                    policy_learn = pl,
                    q_models = q_glm(),
                    g_models = g_glm(),
                    M = 2) # number of folds for cross-fitting

# Getting the cross-fitted actions dictated by the fitted policy:
head(get_policy_actions(pe))
```

get_policy_functions.blip

Get Policy Functions

Description

`get_policy_functions()` returns a function defining the policy at the given stage. `get_policy_functions()` is useful when implementing the learned policy.

Usage

```
## S3 method for class 'blip'
get_policy_functions(
  object,
  stage,
  threshold = NULL,
  include_g_values = FALSE,
  ...
```

```

)
## S3 method for class 'drql'
get_policy_functions(
  object,
  stage,
  threshold = NULL,
  include_g_values = FALSE,
  ...
)
get_policy_functions(object, stage, threshold, ...)

## S3 method for class 'ptl'
get_policy_functions(object, stage, threshold = NULL, ...)

## S3 method for class 'ql'
get_policy_functions(
  object,
  stage,
  threshold = NULL,
  include_g_values = FALSE,
  ...
)

```

Arguments

<code>object</code>	Object of class "policy_object" or "policy_eval", see policy_learn and policy_eval .
<code>stage</code>	Integer. Stage number.
<code>threshold</code>	Numeric, threshold for not choosing the reference action at stage 1.
<code>include_g_values</code>	If TRUE, the g-values are included as an attribute.
<code>...</code>	Additional arguments.

Value

Functions with arguments:

H `data.table::data.table` containing the variables needed to evaluate the policy (and g-function).

Examples

```

library("polle")
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  baseline = "BB",
  covariates = list(L = c("L_1", "L_2")),

```

```

C = c("C_1", "C_2")),
utility = c("U_1", "U_2", "U_3"))
pd

### Realistic V-restricted Policy Tree Learning
# specifying the learner:
pl <- policy_learn(type = "ptl",
                      control = control_ptl(policy_vars = list(c("C_1", "BB"),
                                                               c("L_1", "BB"))),
                      full_history = TRUE,
                      alpha = 0.05)

# evaluating the learner:
pe <- policy_eval(policy_data = pd,
                    policy_learn = pl,
                    q_models = q_glm(),
                    g_models = g_glm())

# getting the policy function at stage 2:
pf2 <- get_policy_functions(pe, stage = 2)
args(pf2)

# applying the policy function to new data:
set.seed(1)
L_1 <- rnorm(n = 10)
new_H <- data.frame(C = rnorm(n = 10),
                      L = L_1,
                      L_1 = L_1,
                      BB = "group1")
d2 <- pf2(H = new_H)
head(d2)

```

`get_policy_object` *Get Policy Object*

Description

Extract the fitted policy object.

Usage

`get_policy_object(object)`

Arguments

<code>object</code>	Object of class <code>policy_eval</code> .
---------------------	--

Value

Object of class `policy_object`.

Examples

```

library("polle")
### Single stage:
d1 <- sim_single_stage(5e2, seed=1)
pd1 <- policy_data(d1, action="A", covariates=list("Z", "B", "L"), utility="U")
pd1

# evaluating the policy:
pe1 <- policy_eval(policy_data = pd1,
                     policy_learn = policy_learn(type = "drql",
                                                  control = control_drql(qv_models = q_glm(~.))),
                     g_models = g_glm(),
                     q_models = q_glm())

# extracting the policy object:
get_policy_object(pe1)

```

get_q_functions*Get Q-functions***Description**

`get_q_functions()` returns a list of (fitted) Q-functions associated with each stage.

Usage

```
get_q_functions(object)
```

Arguments

`object` Object of class `policy_eval` or `policy_object`.

Value

List of class `nuisance_functions`.

See Also

[predict.nuisance_functions](#)

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed = 1)
pd <- policy_data(d,
                  action = c("A_1", "A_2"),
                  baseline = c("B"),
                  covariates = list(

```

```

L = c("L_1", "L_2"),
C = c("C_1", "C_2")
),
utility = c("U_1", "U_2", "U_3")
)
pd

# evaluating the static policy a=1 using outcome regression
# based on a GLM model at each stage.
pe <- policy_eval(
  type = "or",
  policy_data = pd,
  policy = policy_def(1, reuse = TRUE, name = "A=1"),
  q_models = list(q_glm(), q_glm())
)
pe

# getting the Q-functions
q_functions <- get_q_functions(pe)

# getting the fitted g-function values
head(predict(q_functions, pd))

```

get_stage_action_sets *Get Stage Action Sets*

Description

`get_stage_action_sets` returns the action sets at each stage, i.e., the possible actions at each stage for the policy data object.

Usage

```
get_stage_action_sets(object)
```

Arguments

object	Object of class <code>policy_data</code> .
--------	--

Value

List of character vectors.

Examples

```

### Two stages:
d <- sim_two_stage_multi_actions(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                  action = c("A_1", "A_2"),

```

```

baseline = c("B"),
covariates = list(L = c("L_1", "L_2"),
                  C = c("C_1", "C_2")),
utility = c("U_1", "U_2", "U_3"))
pd

# getting the stage actions set:
get_stage_action_sets(pd)

```

get_utility*Get the Utility***Description**

`get_utility()` returns the utility, i.e., the sum of the rewards, for every observation in the policy data object.

Usage

```
get_utility(object)
```

Arguments

object	Object of class <code>policy_data</code> .
--------	--

Value

`data.table::data.table` with key id and numeric variable U.

Examples

```

### Two stages:
d <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("B"),
                   covariates = list(L = c("L_1", "L_2"),
                                     C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

# getting the utility:
head(get_utility(pd))

```

g_model	<i>g_model class object</i>
---------	-----------------------------

Description

Use g_glm(), g_empir(), g_glmnet(), g_rf(), g_sl(), g_xgboost to construct an action probability model/g-model object. The constructors are used as input for `policy_eval()` and `policy_learn()`.

Usage

```
g_empir(formula = ~1, ...)

g_glm(
  formula = ~.,
  family = "binomial",
  model = FALSE,
  na.action = na.pass,
  ...
)

g_glmnet(formula = ~., family = "binomial", alpha = 1, s = "lambda.min", ...)

g_rf(
  formula = ~.,
  num.trees = c(500),
  mtry = NULL,
  cv_args = list(nfolds = 5, rep = 1),
  ...
)

g_sl(
  formula = ~.,
  SL.library = c("SL.mean", "SL.glm"),
  family = binomial(),
  env = as.environment("package:SuperLearner"),
  onlySL = TRUE,
  ...
)

g_xgboost(
  formula = ~.,
  objective = "binary:logistic",
  params = list(),
  nrounds,
  max_depth = 6,
  eta = 0.3,
  nthread = 1,
```

```
cv_args = list(nfolds = 3, rep = 1)
)
```

Arguments

<code>formula</code>	An object of class formula specifying the design matrix for the propensity model/g-model. Use get_history_names() to view the available variable names.
<code>...</code>	Additional arguments passed to glm() , glmnet::glmnet , ranger::ranger or SuperLearner::SuperLearner .
<code>family</code>	A description of the error distribution and link function to be used in the model.
<code>model</code>	(Only used by <code>g_glm</code>) If FALSE model frame will not be saved.
<code>na.action</code>	(Only used by <code>g_glm</code>) A function which indicates what should happen when the data contain NAs, see na.pass .
<code>alpha</code>	(Only used by <code>g_glmnet</code>) The elastic net mixing parameter between 0 and 1. alpha equal to 1 is the lasso penalty, and alpha equal to 0 the ridge penalty.
<code>s</code>	(Only used by <code>g_glmnet</code>) Value(s) of the penalty parameter lambda at which predictions are required, see glmnet::predict.glmnet() .
<code>num.trees</code>	(Only used by <code>g_rf</code>) Number of trees.
<code>mtry</code>	(Only used by <code>g_rf</code>) Number of variables to possibly split at in each node.
<code>cv_args</code>	(Only used by <code>g_rf</code> and <code>g_xgboost</code>) Cross-validation parameters. Only used if multiple hyper-parameters are given. K is the number of folds and rep is the number of replications.
<code>SL.library</code>	(Only used by <code>g_s1</code>) Either a character vector of prediction algorithms or a list containing character vectors, see SuperLearner::SuperLearner .
<code>env</code>	(Only used by <code>g_s1</code>) Environment containing the learner functions. Defaults to the calling environment.
<code>onlySL</code>	(Only used by <code>g_s1</code>) Logical. If TRUE, only saves and computes predictions for algorithms with non-zero coefficients in the super learner object.
<code>objective</code>	(Only used by <code>g_xgboost</code>) specify the learning task and the corresponding learning objective, see xgboost::xgboost .
<code>params</code>	(Only used by <code>g_xgboost</code>) list of parameters.
<code>nrounds</code>	(Only used by <code>g_xgboost</code>) max number of boosting iterations.
<code>max_depth</code>	(Only used by <code>g_xgboost</code>) maximum depth of a tree.
<code>eta</code>	(Only used by <code>g_xgboost</code>) learning rate.
<code>nthread</code>	(Only used by <code>g_xgboost</code>) number of threads.

Details

`g_glm()` is a wrapper of [glm\(\)](#) (generalized linear model).

`g_empir()` calculates the empirical probabilities within the groups defined by the formula.

`g_glmnet()` is a wrapper of [glmnet::glmnet\(\)](#) (generalized linear model via penalized maximum likelihood).

`g_rf()` is a wrapper of [ranger::ranger\(\)](#) (random forest). When multiple hyper-parameters are given, the model with the lowest cross-validation error is selected.

`g_s1()` is a wrapper of [SuperLearner::SuperLearner](#) (ensemble model).

`g_xgboost()` is a wrapper of [xgboost::xgboost](#).

Value

g-model object: function with arguments 'A' (action vector), 'H' (history matrix) and 'action_set'.

See Also

[get_history_names\(\)](#), [get_g_functions\(\)](#).

Examples

```
library("polle")
### Two stages:
d <- sim_two_stage(2e2, seed=1)
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("B"),
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

# available state history variable names:
get_history_names(pd)
# defining a g-model:
g_model <- g_glm(formula = ~B+C)

# evaluating the static policy (A=1) using inverse propensity weighting
# based on a state glm model across all stages:
pe <- policy_eval(type = "ipw",
                    policy_data = pd,
                    policy = policy_def(1, reuse = TRUE),
                    g_models = g_model)
# inspecting the fitted g-model:
get_g_functions(pe)

# available full history variable names at each stage:
get_history_names(pd, stage = 1)
get_history_names(pd, stage = 2)

# evaluating the same policy based on a full history
# glm model for each stage:
pe <- policy_eval(type = "ipw",
                    policy_data = pd,
                    policy = policy_def(1, reuse = TRUE),
                    g_models = list(g_glm(~ L_1 + B),
                                   g_glm(~ A_1 + L_2 + B)),
                    g_full_history = TRUE)
# inspecting the fitted g-models:
get_g_functions(pe)
```

history*Get History Object*

Description

`get_history` summarizes the history and action at a given stage from a [policy_data](#) object.

Usage

```
get_history(object, stage = NULL, full_history = FALSE)
```

Arguments

<code>object</code>	Object of class policy_data .
<code>stage</code>	Stage number. If <code>NULL</code> , the state/Markov-type history across all stages is returned.
<code>full_history</code>	Logical. If <code>TRUE</code> , the full history is returned. If <code>FALSE</code> , only the state/Markov-type history is returned.

Details

Each observation has the sequential form

$$O = B, U_1, X_1, A_1, \dots, U_K, X_K, A_K, U_{K+1},$$

for a possibly stochastic number of stages K.

- B is a vector of baseline covariates.
- U_k is the reward at stage k (not influenced by the action A_k).
- X_k is a vector of state covariates summarizing the state at stage k.
- A_k is the categorical action at stage k.

Value

Object of class [history](#). The object is a list containing the following elements:

<code>H</code>	<code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> and with variables $\{B, X_k\}$ (state history) or $\{B, X_1, A_1, \dots, X_k\}$ (full history), see details.
<code>A</code>	<code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> and variable A_k , see details.
<code>action_name</code>	Name of the action variable in <code>A</code> .
<code>action_set</code>	Sorted character vector defining the action set.
<code>U</code>	(If <code>stage</code> is not <code>NULL</code>) <code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> and with variables U_{bar} and U_{Aa} for every a in the actions set. U_{bar} is the accumulated rewards up till and including the given stage, i.e., $\sum_{j=1}^k U_j$. U_{Aa} is the deterministic reward of action a .

Examples

```

library("polle")
### Single stage:
d1 <- sim_single_stage(5e2, seed=1)
# constructing policy_data object:
pd1 <- policy_data(d1, action="A", covariates=list("Z", "B", "L"), utility="U")
pd1

# In the single stage case, set stage = NULL
h1 <- get_history(pd1)
head(h1$H)
head(h1$A)

### Two stages:
d2 <- sim_two_stage(5e2, seed=1)
# constructing policy_data object:
pd2 <- policy_data(d2,
                    action = c("A_1", "A_2"),
                    baseline = c("B"),
                    covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                    utility = c("U_1", "U_2", "U_3"))
pd2
# getting the state/Markov-type history across all stages:
h2 <- get_history(pd2)
head(h2$H)
head(h2$A)

# getting the full history at stage 2:
h2 <- get_history(pd2, stage = 2, full_history = TRUE)
head(h2$H)
head(h2$A)
head(h2$U)

# getting the state/Markov-type history at stage 2:
h2 <- get_history(pd2, stage = 2, full_history = FALSE)
head(h2$H)
head(h2$A)

### Multiple stages
d3 <- sim_multi_stage(5e2, seed = 1)
# constructing policy_data object:
pd3 <- policy_data(data = d3$stage_data,
                    baseline_data = d3$baseline_data,
                    type = "long",
                    id = "id",
                    stage = "stage",
                    event = "event",
                    action = "A",
                    utility = "U")
pd3

```

```
# getting the full history at stage 2:
h3 <- get_history(pd3, stage = 2, full_history = TRUE)
head(h3$H)
# note that not all observations have two stages:
nrow(h3$H) # number of observations with two stages.
get_n(pd3) # number of observations in total.
```

Description

The fitted g-functions and Q-functions are stored in an object of class "nuisance_functions". The object is a list with a fitted model object for every stage. Information on whether the full history or the state/Markov-type history is stored as an attribute ("full_history").

S3 generics

The following S3 generic functions are available for an object of class `nuisance_functions`:

`predict` Predict the values of the g- or Q-functions based on a `policy_data` object.

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
                  action = c("A_1", "A_2"),
                  covariates = list(L = c("L_1", "L_2"),
                                     C = c("C_1", "C_2")),
                  utility = c("U_1", "U_2", "U_3"))
pd

# evaluating the static policy a=1:
pe <- policy_eval(policy_data = pd,
                    policy = policy_def(1, reuse = TRUE),
                    g_models = g_glm(),
                    q_models = q_glm())

# getting the fitted g-functions:
(g_functions <- get_g_functions(pe))

# getting the fitted Q-functions:
(q_functions <- get_q_functions(pe))

# getting the fitted values:
head(predict(g_functions, pd))
head(predict(q_functions, pd))
```

partial	<i>Trim Number of Stages</i>
---------	------------------------------

Description

partial creates a partial policy data object by trimming the maximum number of stages in the policy data object to a fixed given number.

Usage

```
partial(object, K)
```

Arguments

object	Object of class policy_data .
K	Maximum number of stages.

Value

Object of class [policy_data](#).

Examples

```
library("polle")
### Multiple stage case
d <- sim_multi_stage(5e2, seed = 1)
# constructing policy_data object:
pd <- policy_data(data = d$stage_data,
                   baseline_data = d$baseline_data,
                   type = "long",
                   id = "id",
                   stage = "stage",
                   event = "event",
                   action = "A",
                   utility = "U")
pd
# Creating a partial policy data object with 3 stages
pd3 <- partial(pd, K = 3)
pd3
```

`plot.policy_data` *Plot policy data for given policies*

Description

Plot policy data for given policies

Usage

```
## S3 method for class 'policy_data'
plot(
  x,
  policy = NULL,
  which = c(1),
  stage = 1,
  history_variables = NULL,
  jitter = 0.05,
  ...
)
```

Arguments

<code>x</code>	Object of class policy_data
<code>policy</code>	An object or list of objects of class policy
<code>which</code>	A subset of the numbers 1:2 <ul style="list-style-type: none"> • 1 Spaghetti plot of the cumulative rewards • 2 Plot of the policy actions for a given stage
<code>stage</code>	Stage number for plot 2
<code>history_variables</code>	character vector of length 2 for plot 2
<code>jitter</code>	numeric
<code>...</code>	Additional arguments

Examples

```
library("polle")
library("data.table")
setDTthreads(1)
d3 <- sim_multi_stage(2e2, seed = 1)
pd3 <- policy_data(data = d3$stage_data,
                     baseline_data = d3$baseline_data,
                     type = "long",
                     id = "id",
                     stage = "stage",
                     event = "event",
                     action = "A",
```

```

        utility = "U")

# specifying two static policies:
p0 <- policy_def(c(1,1,0,0), name = "p0")
p1 <- policy_def(c(1,0,0,0), name = "p1")

plot(pd3)
plot(pd3, policy = list(p0, p1))

# learning and plotting a policy:
pe3 <- policy_eval(pd3,
                     policy_learn = policy_learn(),
                     q_models = q_glm(formula = ~t + X + X_lead))
plot(pd3, list(get_policy(pe3), p0))

# plotting the recommended actions at a specific stage:
plot(pd3, get_policy(pe3),
      which = 2,
      stage = 2,
      history_variables = c("t","X"))

```

plot.policy_eval*Plot histogram of the influence curve for a policy_eval object*

Description

Plot histogram of the influence curve for a policy_eval object

Usage

```
## S3 method for class 'policy_eval'
plot(x, ...)
```

Arguments

<code>x</code>	Object of class policy_eval
<code>...</code>	Additional arguments

Examples

```

d <- sim_two_stage(2e3, seed=1)
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = "BB",
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))

pe <- policy_eval(pd,
```

```
policy_learn = policy_learn()
plot(pe)
```

policy

Policy-class

Description

A function of inherited class "policy" takes a policy data object as input and returns the policy actions for every observation for every (observed) stage.

Details

A policy can either be defined directly by the user using [policy_def](#) or a policy can be fitted using [policy_learn](#) (or [policy_eval](#)). [policy_learn](#) returns a [policy_object](#) from which the policy can be extracted using [get_policy](#).

Value

[data.table::data.table](#) with keys id and stage and action variable d.

S3 generics

The following S3 generic functions are available for an object of class *policy*:

`print` Basic print function

Examples

```
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
  action = c("A_1", "A_2"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

# defining a dynamic policy:
p <- policy_def(
  function(L) (L>0)*1,
  reuse = TRUE
)
p
head(p(pd), 5)

# V-restricted (Doubly Robust) Q-learning:
# specifying the learner:
pl <- policy_learn(type = "drql",
  control = control_drql(qv_models = q_glm(formula = ~ C)))
```

```
# fitting the policy (object):
po <- pl(policy_data = pd,
         q_models = q_glm(),
         g_models = g_glm())

p <- get_policy(po)
p

head(p(pd))
```

policy_data*Create Policy Data Object***Description**

`policy_data()` creates a policy data object which is used as input to `policy_eval()` and `policy_learn()` for policy evaluation and data adaptive policy learning.

Usage

```
policy_data(
  data,
  baseline_data,
  type = "wide",
  action,
  covariates,
  utility,
  baseline = NULL,
  deterministic_rewards = NULL,
  id = NULL,
  stage = NULL,
  event = NULL,
  action_set = NULL,
  verbose = FALSE
)

## S3 method for class 'policy_data'
print(x, digits = 2, ...)

## S3 method for class 'policy_data'
summary(object, probs = seq(0, 1, 0.25), ...)
```

Arguments

`data` `data.frame` or `data.table::data.table`; see Examples.
`baseline_data` `data.frame` or `data.table::data.table`; see Examples.

type	Character string. If "wide", data is considered to be on wide format. If "long", data is considered to be on long format; see Examples.
action	Action variable name(s). Character vector or character string. <ul style="list-style-type: none"> • A vector is valid for wide data. The length of the vector determines the number of stages (K). • A string is valid for single stage wide data or long data.
covariates	Stage specific covariate name(s). Character vector or named list of character vectors. <ul style="list-style-type: none"> • A vector is valid for single stage wide data or long data. • A named list is valid for multiple stages wide data. Each element must be a character vector with length K. Each vector can contain NA elements, if a covariate is not available for the given stage(s).
utility	Utility/Reward variable name(s). Character string or vector. <ul style="list-style-type: none"> • A string is valid for long data and wide data with a single final utility. • A vector is valid for wide data with incremental rewards. Must have length K+1; see Examples.
baseline	Baseline covariate name(s). Character vector.
deterministic_rewards	Deterministic reward variable name(s). Named list of character vectors of length K. The name of each element must be on the form "U_Aa" where "a" corresponds to an action in the action set.
id	ID variable name. Character string.
stage	Stage number variable name.
event	Event indicator name.
action_set	Character string. Action set across all stages.
verbose	Logical. If TRUE, formatting comments are printed to the console.
x	Object to be printed.
digits	Minimum number of digits to be printed.
...	Additional arguments passed to print.
object	Object of class <i>policy_data</i>
probs	numeric vector (probabilities)

Details

Each observation has the sequential form

$$O = B, U_1, X_1, A_1, \dots, U_K, X_K, A_K, U_{K+1},$$

for a possibly stochastic number of stages K.

- B is a vector of baseline covariates.
- U_k is the reward at stage k (not influenced by the action A_k).
- X_k is a vector of state covariates summarizing the state at stage k.
- A_k is the categorical action at stage k.

The utility is given by the sum of the rewards, i.e., $U = \sum_{k=1}^{K+1} U_k$.

Value

`policy_data()` returns an object of class "policy_data". The object is a list containing the following elements:

<code>stage_data</code>	<code>data.table::data.table</code> containing the id, stage number, event indicator, action (A_k), state covariates (X_k), reward (U_k), and the deterministic rewards.
<code>baseline_data</code>	<code>data.table::data.table</code> containing the id and baseline covariates (B).
<code>colnames</code>	List containing the state covariate names, baseline covariate names, and the deterministic reward variable names.
<code>action_set</code>	Sorted character vector describing the action set, i.e., the possible actions at all stages.
<code>stage_action_sets</code>	List of sorted character vectors describing the observed actions at each stage.
<code>dim</code>	List containing the number of observations (n) and the number of stages (K).

S3 generics

The following S3 generic functions are available for an object of class `policy_data`:

- `partial()` Trim the maximum number of stages in a `policy_data` object.
- `subset_id()` Subset a `policy_data` object on ID.
- `get_history()` Summarize the history and action at a given stage.
- `get_history_names()` Get history variable names.
- `get_actions()` Get the action at every stage.
- `get_utility()` Get the utility.
- `plot()` Plot method.

See Also

`policy_eval()`, `policy_learn()`, `copy_policy_data()`

Examples

```
library("polle")
### Single stage: Wide data
d1 <- sim_single_stage(n = 5e2, seed=1)
head(d1, 5)
# constructing policy_data object:
pd1 <- policy_data(d1,
                     action="A",
                     covariates=c("Z", "B", "L"),
                     utility="U")
pd1
# associated S3 methods:
methods(class = "policy_data")
head(get_actions(pd1), 5)
head(get_utility(pd1), 5)
```

```

head(get_history(pd1)$H, 5)

### Two stage: Wide data
d2 <- sim_two_stage(5e2, seed=1)
head(d2, 5)
# constructing policy_data object:
pd2 <- policy_data(d2,
                     action = c("A_1", "A_2"),
                     baseline = c("B"),
                     covariates = list(L = c("L_1", "L_2"),
                                        C = c("C_1", "C_2")),
                     utility = c("U_1", "U_2", "U_3"))
pd2
head(get_history(pd2, stage = 2)$H, 5) # state/Markov type history and action, (H_k,A_k).
head(get_history(pd2, stage = 2, full_history = TRUE)$H, 5) # Full history and action, (H_k,A_k).

### Multiple stages: Long data
d3 <- sim_multi_stage(5e2, seed = 1)
head(d3$stage_data, 10)
# constructing policy_data object:
pd3 <- policy_data(data = d3$stage_data,
                     baseline_data = d3$baseline_data,
                     type = "long",
                     id = "id",
                     stage = "stage",
                     event = "event",
                     action = "A",
                     utility = "U")
pd3
head(get_history(pd3, stage = 3)$H, 5) # state/Markov type history and action, (H_k,A_k).
head(get_history(pd3, stage = 2, full_history = TRUE)$H, 5) # Full history and action, (H_k,A_k).

```

policy_def*Define Policy***Description**

`policy_def` returns a function of class `policy`. The function input is a `policy_data` object and it returns a `data.table::data.table` with keys `id` and `stage` and `action` variable `d`.

Usage

```
policy_def(policy_functions, full_history = FALSE, reuse = FALSE, name = NULL)
```

Arguments

`policy_functions`

A single function/character string or a list of functions/character strings. The list must have the same length as the number of stages.

`full_history` If TRUE, the full history at each stage is used as input to the policy functions.

reuse	If TRUE, the policy function is reused at every stage.
name	Character string.

Value

Function of class "policy". The function takes a [policy_data](#) object as input and returns a [data.table::data.table](#) with keys id and stage and action variable d.

See Also

[get_history_names\(\)](#), [get_history\(\)](#).

Examples

```
library("polle")
### Single stage"
d1 <- sim_single_stage(5e2, seed=1)
pd1 <- policy_data(d1, action="A", covariates=list("Z", "B", "L"), utility="U")
pd1

# defining a static policy (A=1):
p1_static <- policy_def(1)

# applying the policy:
p1_static(pd1)

# defining a dynamic policy:
p1_dynamic <- policy_def(
  function(Z, L) ((3*Z + 1*L -2.5)>0)*1
)
p1_dynamic(pd1)

### Two stages:
d2 <- sim_two_stage(5e2, seed = 1)
pd2 <- policy_data(d2,
  action = c("A_1", "A_2"),
  covariates = list(L = c("L_1", "L_2"),
    C = c("C_1", "C_2")),
  utility = c("U_1", "U_2", "U_3"))

# defining a static policy (A=0):
p2_static <- policy_def(0,
  reuse = TRUE)
p2_static(pd2)

# defining a reused dynamic policy:
p2_dynamic_reuse <- policy_def(
  function(L) (L > 0)*1,
  reuse = TRUE
)
p2_dynamic_reuse(pd2)
```

```
# defining a dynamic policy for each stage based on the full history:
# available variable names at each stage:
get_history_names(pd2, stage = 1)
get_history_names(pd2, stage = 2)

p2_dynamic <- policy_def(
  policy_functions = list(
    function(L_1) (L_1 > 0)*1,
    function(L_1, L_2) (L_1 + L_2 > 0)*1
  ),
  full_history = TRUE
)
p2_dynamic(pd2)
```

policy_eval*Policy Evaluation***Description**

`policy_eval()` is used to estimate the value of a given fixed policy or a data adaptive policy (e.g. a policy learned from the data). `policy_eval()` is also used to estimate the average treatment effect among the subjects who would get the treatment under the policy.

Usage

```
policy_eval(
  policy_data,
  policy = NULL,
  policy_learn = NULL,
  g_functions = NULL,
  g_models = g_glm(),
  g_full_history = FALSE,
  save_g_functions = TRUE,
  q_functions = NULL,
  q_models = q_glm(),
  q_full_history = FALSE,
  save_q_functions = TRUE,
  target = "value",
  type = "dr",
  cross_fit_type = "pooled",
  variance_type = "pooled",
  M = 1,
  future_args = list(future.seed = TRUE),
  name = NULL
)

## S3 method for class 'policy_eval'
coef(object, ...)
```

```

## S3 method for class 'policy_eval'
IC(x, ...)

## S3 method for class 'policy_eval'
vcov(object, ...)

## S3 method for class 'policy_eval'
print(
  x,
  digits = 4L,
  width = 35L,
  std.error = TRUE,
  level = 0.95,
  p.value = TRUE,
  ...
)

## S3 method for class 'policy_eval'
summary(object, ...)

## S3 method for class 'policy_eval'
estimate(
  x,
  labels = get_element(x, "name", check_name = FALSE),
  level = 0.95,
  ...
)

## S3 method for class 'policy_eval'
merge(x, y, ..., paired = TRUE)

## S3 method for class 'policy_eval'
x + ...

```

Arguments

policy_data	Policy data object created by policy_data() .
policy	Policy object created by policy_def() .
policy_learn	Policy learner object created by policy_learn() .
g_functions	Fitted g-model objects, see nuisance_functions . Preferably, use g_models.
g_models	List of action probability models/g-models for each stage created by g_empir() , g_glm() , g_rf() , g_sl() or similar functions. Only used for evaluation if g_functions is NULL. If a single model is provided and g_full_history is FALSE, a single g-model is fitted across all stages. If g_full_history is TRUE the model is reused at every stage.
g_full_history	If TRUE, the full history is used to fit each g-model. If FALSE, the state/Markov type history is used to fit each g-model.

<code>save_g_functions</code>	If TRUE, the fitted g-functions are saved.
<code>q_functions</code>	Fitted Q-model objects, see nuisance_functions . Only valid if the Q-functions are fitted using the same policy. Preferably, use <code>q_models</code> .
<code>q_models</code>	Outcome regression models/Q-models created by <code>q_glm()</code> , <code>q_rf()</code> , <code>q_s1()</code> or similar functions. Only used for evaluation if <code>q_functions</code> is NULL. If a single model is provided, the model is reused at every stage.
<code>q_full_history</code>	Similar to <code>g_full_history</code> .
<code>save_q_functions</code>	Similar to <code>save_g_functions</code> .
<code>target</code>	Character string. Either "value" or "subgroup". If "value", the target parameter is the policy value. If "subgroup", the target parameter is the average treatment effect among the subgroup of subjects that would receive treatment under the policy, see details. "subgroup" is only implemented for <code>type = "dr"</code> in the single-stage case with a dichotomous action set.
<code>type</code>	Character string. Type of evaluation. Either "dr" (doubly robust), "ipw" (inverse propensity weighting), or "or" (outcome regression).
<code>cross_fit_type</code>	Character string. Either "stacked", or "pooled", see details. (Only used if <code>M > 1</code> and <code>target = "subgroup"</code>)
<code>variance_type</code>	Character string. Either "pooled" (default), "stacked" or "complete", see details. (Only used if <code>M > 1</code>)
<code>M</code>	Number of folds for cross-fitting.
<code>future_args</code>	Arguments passed to future.apply::future_apply() .
<code>name</code>	Character string.
<code>object, x, y</code>	Objects of class "policy_eval".
<code>...</code>	Additional arguments.
<code>digits</code>	Integer. Number of printed digits.
<code>width</code>	Integer. Width of printed parameter name.
<code>std.error</code>	Logical. Should the std.error be printed.
<code>level</code>	Numeric. Level of confidence limits.
<code>p.value</code>	Logical. Should the p.value for associated confidence level be printed.
<code>labels</code>	Name(s) of the estimate(s).
<code>paired</code>	TRUE indicates that the estimates are based on the same data sample.

Details

Each observation has the sequential form

$$O = B, U_1, X_1, A_1, \dots, U_K, X_K, A_K, U_{K+1},$$

for a possibly stochastic number of stages K.

- B is a vector of baseline covariates.

- U_k is the reward at stage k (not influenced by the action A_k).
- X_k is a vector of state covariates summarizing the state at stage k.
- A_k is the categorical action within the action set \mathcal{A} at stage k.

The utility is given by the sum of the rewards, i.e., $U = \sum_{k=1}^{K+1} U_k$.

A policy is a set of functions

$$d = \{d_1, \dots, d_K\},$$

where d_k for $k \in \{1, \dots, K\}$ maps $\{B, X_1, A_1, \dots, A_{k-1}, X_k\}$ into the action set.

Recursively define the Q-models (q_models):

$$Q_K^d(h_K, a_K) = E[U|H_K = h_K, A_K = a_K]$$

$$Q_k^d(h_k, a_k) = E[Q_{k+1}(H_{k+1}, d_{k+1}(B, X_1, A_1, \dots, X_k))|H_k = h_k, A_k = a_k].$$

If q_full_history = TRUE, $H_k = \{B, X_1, A_1, \dots, A_{k-1}, X_k\}$, and if q_full_history = FALSE, $H_k = \{B, X_k\}$.

The g-models (g_models) are defined as

$$g_k(h_k, a_k) = P(A_k = a_k|H_k = h_k).$$

If g_full_history = TRUE, $H_k = \{B, X_1, A_1, \dots, A_{k-1}, X_k\}$, and if g_full_history = FALSE, $H_k = \{B, X_k\}$. Furthermore, if g_full_history = FALSE and g_models is a single model, it is assumed that $g_1(h_1, a_1) = \dots = g_K(h_K, a_K)$.

If target = "value" and type = "or" policy_eval() returns the empirical estimate of the value (coef):

$$E [Q_1^d(H_1, d_1(\cdot))]$$

If target = "value" and type = "ipw" policy_eval() returns the empirical estimates of the value (coef) and influence curve (IC):

$$E \left[\left(\prod_{k=1}^K I\{A_k = d_k(\cdot)\} g_k(H_k, A_k)^{-1} \right) U \right].$$

$$\left(\prod_{k=1}^K I\{A_k = d_k(\cdot)\} g_k(H_k, A_k)^{-1} \right) U - E \left[\left(\prod_{k=1}^K I\{A_k = d_k(\cdot)\} g_k(H_k, A_k)^{-1} \right) U \right].$$

If target = "value" and type = "dr" policy_eval returns the empirical estimates of the value (coef) and influence curve (IC):

$$E[Z_1(d, g, Q^d)(O)],$$

$$Z_1(d, g, Q^d)(O) - E[Z_1(d, g, Q^d)(O)],$$

where

$$Z_1(d, g, Q^d)(O) = Q_1^d(H_1, d_1(\cdot)) + \sum_{r=1}^K \prod_{j=1}^r \frac{I\{A_j = d_j(\cdot)\}}{g_j(H_j, A_j)} \{Q_{r+1}^d(H_{r+1}, d_{r+1}(\cdot)) - Q_r^d(H_r, d_r(\cdot))\}.$$

If `target = "subgroup"`, `type = "dr"`, $K = 1$, and $\mathcal{A} = \{0, 1\}$, `policy_eval()` returns the empirical estimates of the subgroup average treatment effect (`coef`) and influence curve (IC):

$$E[Z_1(1, g, Q)(O) - Z_1(0, g, Q)(O)|d_1(\cdot) = 1],$$

$$\frac{1}{P(d_1(\cdot) = 1)} I\{d_1(\cdot) = 1\} \left\{ Z_1(1, g, Q)(O) - Z_1(0, g, Q)(O) - E[Z_1(1, g, Q)(O) - Z_1(0, g, Q)(O)|d_1(\cdot) = 1] \right\}.$$

Applying M -fold cross-fitting using the `{M}` argument, let

$$\mathcal{Z}_{1,m}(a) = \{Z_1(a, g_m, Q_m^d)(O) : O \in \mathcal{O}_m\}.$$

If `target = "subgroup"`, `type = "dr"`, $K = 1$, $\mathcal{A} = \{0, 1\}$, and `cross_fit_type = "pooled"`, `policy_eval()` returns the estimate

$$\frac{1}{N^{-1} \sum_{i=1}^N I\{d(H_i) = 1\}} N^{-1} \sum_{m=1}^M \sum_{(Z,H) \in \mathcal{Z}_{1,m} \times \mathcal{H}_{1,m}} I\{d_1(H) = 1\} \{Z(1) - Z(0)\}$$

If `cross_fit_type = "stacked"` the returned estimate is

$$M^{-1} \sum_{m=1}^M \frac{1}{n^{-1} \sum_{h \in \mathcal{H}_{1,m}} I\{d(h) = 1\}} n^{-1} \sum_{(Z,H) \in \mathcal{Z}_{1,m} \times \mathcal{H}_{1,m}} I\{d_1(H) = 1\} \{Z(1) - Z(0)\},$$

where for ease of notation we let the integer n be the number of observations in each fold.

Value

`policy_eval()` returns an object of class "policy_eval". The object is a list containing the following elements:

<code>coef</code>	Numeric vector. The estimated target parameter: policy value or subgroup average treatment effect.
<code>IC</code>	Numeric matrix. Estimated influence curve associated with <code>coef</code> .
<code>type</code>	Character string. The type of evaluation ("dr", "ipw", "or").
<code>target</code>	Character string. The target parameter ("value" or "subgroup")
<code>id</code>	Character vector. The IDs of the observations.
<code>name</code>	Character vector. Names for the each element in <code>coef</code> .
<code>coef_ipw</code>	(only if <code>type = "dr"</code>) Numeric vector. Estimate of <code>coef</code> based solely on inverse probability weighting.
<code>coef_or</code>	(only if <code>type = "dr"</code>) Numeric vector. Estimate of <code>coef</code> based solely on outcome regression.
<code>policy_actions</code>	<code>data.table::data.table</code> with keys <code>id</code> and <code>stage</code> . Actions associated with the policy for every observation and stage.
<code>policy_object</code>	(only if <code>policy = NULL</code> and <code>M = 1</code>) The policy object returned by <code>policy_learn</code> , see <code>policy_learn</code> .
<code>g_functions</code>	(only if <code>M = 1</code>) The fitted g-functions. Object of class "nuisance_functions".

g_values	The fitted g-function values.
q_functions	(only if M = 1) The fitted Q-functions. Object of class "nuisance_functions".
q_values	The fitted Q-function values.
Z	(only if target = "subgroup") Matrix with the doubly robust stage 1 scores for each action.
subgroup_indicator	(only if target = "subgroup") Logical matrix identifying subjects in the subgroup. Each column represents a different subgroup threshold.
cross_fits	(only if M > 1) List containing the "policy_eval" object for every (validation) fold.
folds	(only if M > 1) The (validation) folds used for cross-fitting.
cross_fit_type	Character string.
variance_type	Character string.

S3 generics

The following S3 generic functions are available for an object of class `policy_eval`:

- `get_g_functions()` Extract the fitted g-functions.
- `get_q_functions()` Extract the fitted Q-functions.
- `get_policy()` Extract the fitted policy object.
- `get_policy_functions()` Extract the fitted policy function for a given stage.
- `get_policy_actions()` Extract the (fitted) policy actions.
- `plot.policy_eval()` Plot diagnostics.

References

van der Laan, Mark J., and Alexander R. Luedtke. "Targeted learning of the mean outcome under an optimal dynamic treatment rule." Journal of causal inference 3.1 (2015): 61-95. [doi:10.1515/jci-20130022](https://doi.org/10.1515/jci-20130022)

Tsiatis, Anastasios A., et al. Dynamic treatment regimes: Statistical methods for precision medicine. Chapman and Hall/CRC, 2019. [doi:10.1201/9780429192692](https://doi.org/10.1201/9780429192692).

Victor Chernozhukov, Denis Chetverikov, Mert Demirer, Esther Duflo, Christian Hansen, Whitney Newey, James Robins, Double/debiased machine learning for treatment and structural parameters, The Econometrics Journal, Volume 21, Issue 1, 1 February 2018, Pages C1–C68, [doi:10.1111/ectj.12097](https://doi.org/10.1111/ectj.12097).

See Also

`lava::IC`, `lava::estimate.default`.

Examples

```

utility = c("U_1", "U_2", "U_3"))
pd2

# defining a policy learner based on cross-fitted doubly robust Q-learning:
pl2 <- policy_learn(
  type = "drql",
  control = control_drql(qv_models = list(q_glm(~C_1),
                                         q_glm(~C_1+C_2))),
  full_history = TRUE,
  L = 2) # number of folds for cross-fitting

# evaluating the policy learner using 2-fold cross fitting:
pe2 <- policy_eval(type = "dr",
                     policy_data = pd2,
                     policy_learn = pl2,
                     q_models = q_glm(),
                     g_models = g_glm(),
                     M = 2, # number of folds for cross-fitting
                     name = "drql")
# summarizing the estimated value of the policy:
pe2

# getting the cross-fitted policy actions:
head(get_policy_actions(pe2))

```

policy_learn*Create Policy Learner***Description**

`policy_learn()` is used to specify a policy learning method (Q-learning, doubly robust Q-learning, policy tree learning and outcome weighted learning). Evaluating the policy learner returns a policy object.

Usage

```

policy_learn(
  type = "ql",
  control = list(),
  alpha = 0,
  threshold = NULL,
  full_history = FALSE,
  L = 1,
  cross_fit_g_models = TRUE,
  save_cross_fit_models = FALSE,
  future_args = list(future.seed = TRUE),
  name = type
)

```

```
## S3 method for class 'policy_learn'
print(x, ...)

## S3 method for class 'policy_object'
print(x, ...)
```

Arguments

type	Type of policy learner method: <ul style="list-style-type: none"> • "ql": Quality/Q-learning. • "drql": Doubly Robust Q-learning. • "blip": Doubly Robust blip-learning (only for dichotomous actions). • "ptl": Policy Tree Learning. • "owl": Outcome Weighted Learning. • "earl": Efficient Augmentation and Relaxation Learning (only single stage). • "rwl": Residual Weighted Learning (only single stage).
control	List of control arguments. Values (and default values) are set using <code>control_{type}()</code> . Key arguments include: <code>control_drql()</code> : <ul style="list-style-type: none"> • qv_models: Single element or list of V-restricted Q-models created by <code>q_glm()</code>, <code>q_rf()</code>, <code>q_sl()</code> or similar functions. <code>control_blip()</code> : <ul style="list-style-type: none"> • blip_models: Single element or list of V-restricted blip-models created by <code>q_glm()</code>, <code>q_rf()</code>, <code>q_sl()</code> or similar functions. <code>control_ptl()</code> : <ul style="list-style-type: none"> • policy_vars: Character vector/string or list of character vectors/strings. Variable names used to construct the V-restricted policy tree. The names must be a subset of the history names, see <code>get_history_names()</code>. • hybrid: If TRUE, <code>policytree::hybrid_policy_tree()</code> is used to fit a policy tree. • depth: Integer or integer vector. The depth of the fitted policy tree for each stage. <code>control_owl()</code> : <ul style="list-style-type: none"> • policy_vars: As in <code>control_ptl()</code>. • loss: Loss function. The options are "hinge", "ramp", "logit", "logit.lasso", "l2", "l2.lasso". • kernel: Type of kernel used by the support vector machine. The options are "linear", "rbf". • augment: If TRUE the outcomes are augmented. <code>control_earl() / control_rwl()</code> :

	<ul style="list-style-type: none"> • <code>moPropen</code>: Propensity model of class "ModelObj", see modelObj::modelObj. • <code>moMain</code>: Main effects outcome model of class "ModelObj". • <code>moCont</code> Contrast outcome model of class "ModelObj". • <code>regime</code>: An object of class formula specifying the design of the policy. • <code>surrogate</code>: The surrogate 0-1 loss function. The options are "logit", "exp", "hinge", "sqhinge", "huber". • <code>kernel</code>: The options are "linear", "poly", "radial".
<code>alpha</code>	Probability threshold for determining realistic actions.
<code>threshold</code>	Numeric vector, thresholds for not choosing the reference action at stage 1.
<code>full_history</code>	If TRUE, the full history is used to fit each policy function (e.g. QV-model, policy tree). If FALSE, the single stage/ "Markov type" history is used to fit each policy function.
<code>L</code>	Number of folds for cross-fitting nuisance models.
<code>cross_fit_g_models</code>	If TRUE, the g-models will not be cross-fitted even if <code>L > 1</code> .
<code>save_cross_fit_models</code>	If TRUE, the cross-fitted models will be saved.
<code>future_args</code>	Arguments passed to future.apply::future_apply() .
<code>name</code>	Character string.
<code>x</code>	Object of class "policy_object" or "policy_learn".
<code>...</code>	Additional arguments passed to print.

Value

Function of inherited class "policy_learn". Evaluating the function on a [policy_data](#) object returns an object of class [policy_object](#). A policy object is a list containing all or some of the following elements:

<code>q_functions</code>	Fitted Q-functions. Object of class "nuisance_functions".
<code>g_functions</code>	Fitted g-functions. Object of class "nuisance_functions".
<code>action_set</code>	Sorted character vector describing the action set, i.e., the possible actions at each stage.
<code>alpha</code>	Numeric. Probability threshold to determine realistic actions.
<code>K</code>	Integer. Maximal number of stages.
<code>qv_functions</code> (only if <code>type = "drql"</code>)	Fitted V-restricted Q-functions. Contains a fitted model for each stage and action.
<code>ptl_objects</code> (only if <code>type = "ptl"</code>)	Fitted V-restricted policy trees. Contains a policytree::policy_tree for each stage.
<code>ptl_designs</code> (only if <code>type = "ptl"</code>)	Specification of the V-restricted design matrix for each stage

S3 generics

The following S3 generic functions are available for an object of class "policy_object":

```
get_g_functions() Extract the fitted g-functions.  

get_q_functions() Extract the fitted Q-functions.  

get_policy() Extract the fitted policy object.  

get_policy_functions() Extract the fitted policy function for a given stage.  

get_policy_actions() Extract the (fitted) policy actions.
```

References

Doubly Robust Q-learning (type = "drql"): Luedtke, Alexander R., and Mark J. van der Laan. "Super-learning of an optimal dynamic treatment rule." *The international journal of biostatistics* 12.1 (2016): 305-332. [doi:10.1515/ijb20150052](https://doi.org/10.1515/ijb20150052).

Policy Tree Learning (type = "ptl"): Zhou, Zhengyuan, Susan Athey, and Stefan Wager. "Offline multi-action policy learning: Generalization and optimization." *Operations Research* (2022). [doi:10.1287/opre.2022.2271](https://doi.org/10.1287/opre.2022.2271).

(Augmented) Outcome Weighted Learning: Liu, Ying, et al. "Augmented outcome-weighted learning for estimating optimal dynamic treatment regimens." *Statistics in medicine* 37.26 (2018): 3776-3788. [doi:10.1002/sim.7844](https://doi.org/10.1002/sim.7844).

See Also

[policy_eval\(\)](#)

Examples

```
library("polle")
### Two stages:
d <- sim_two_stage(5e2, seed=1)
pd <- policy_data(d,
                   action = c("A_1", "A_2"),
                   baseline = c("BB"),
                   covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                   utility = c("U_1", "U_2", "U_3"))
pd

### V-restricted (Doubly Robust) Q-learning

# specifying the learner:
pl <- policy_learn(
  type = "drql",
  control = control_drql(qv_models = list(q_glm(formula = ~ C_1 + BB),
                                            q_glm(formula = ~ L_1 + BB))),
  full_history = TRUE
)
```

```

# evaluating the learned policy
pe <- policy_eval(policy_data = pd,
                    policy_learn = pl,
                    q_models = q_glm(),
                    g_models = g_glm())
pe
# getting the policy object:
po <- get_policy_object(pe)
# inspecting the fitted QV-model for each action strata at stage 1:
po$qv_functions$stage_1
head(get_policy(pe)(pd))

```

predict.nuisance_functions*Predict g-functions and Q-functions***Description**

`predict()` returns the fitted values of the g-functions and Q-functions when applied to a (new) policy data object.

Usage

```
## S3 method for class 'nuisance_functions'
predict(object, new_policy_data, ...)
```

Arguments

- `object` Object of class "nuisance_functions". Either `g_functions` or `q_functions` as returned by `policy_eval()` or `policy_learn()`.
- `new_policy_data` Policy data object created by `policy_data()`.
- `...` Additional arguments.

Value

`data.table::data.table` with keys `id` and `stage` and variables `g_a` or `Q_a` for each action `a` in the actions set.

Examples

```

library("polle")
### Single stage:
d <- sim_single_stage(5e2, seed=1)
pd <- policy_data(d, action="A", covariates=list("Z", "B", "L"), utility="U")
pd
# defining a static policy (A=1):

```

```

pl <- policy_def(1, name = "A=1")

# doubly robust evaluation of the policy:
pe <- policy_eval(policy_data = pd,
                    policy = pl,
                    g_models = g_glm(),
                    q_models = q_glm())
# summarizing the estimated value of the policy:
pe

# getting the fitted g-function values:
head(predict(get_g_functions(pe), pd))

# getting the fitted Q-function values:
head(predict(get_q_functions(pe), pd))

```

q_model

q_model class object

Description

Use `q_glm()`, `q_glmnet()`, `q_rf()`, and `q_sl()` to construct an outcome regression model/Q-model object. The constructors are used as input for `policy_eval()` and `policy_learn()`.

Usage

```

q_glm(
  formula = ~A * .,
  family = gaussian(),
  model = FALSE,
  na.action = na.pass,
  ...
)

q_glmnet(
  formula = ~A * .,
  family = "gaussian",
  alpha = 1,
  s = "lambda.min",
  ...
)

q_rf(
  formula = ~.,
  num.trees = c(250, 500, 750),
  mtry = NULL,
  cv_args = list(nfolds = 3, rep = 1),
  ...
)

```

```

)
q_s1(
  formula = ~.,
  SL.library = c("SL.mean", "SL.glm"),
  env = as.environment("package:SuperLearner"),
  onlySL = TRUE,
  discreteSL = FALSE,
  ...
)
q_xgboost(
  formula = ~.,
  objective = "reg:squarederror",
  params = list(),
  nrounds,
  max_depth = 6,
  eta = 0.3,
  nthread = 1,
  cv_args = list(nfolds = 3, rep = 1)
)

```

Arguments

formula	An object of class formula specifying the design matrix for the outcome regression model/Q-model at the given stage. The action at the given stage is always denoted 'A', see examples. Use get_history_names() to see the additional available variable names.
family	A description of the error distribution and link function to be used in the model.
model	(Only used by q_glm) If FALSE model frame will not be saved.
na.action	(Only used by q_glm) A function which indicates what should happen when the data contain NAs, see na.pass .
...	Additional arguments passed to glm() , glmnet::glmnet , ranger::ranger or SuperLearner::SuperLearner .
alpha	(Only used by q_glmnet) The elasticnet mixing parameter between 0 and 1. alpha equal to 1 is the lasso penalty, and alpha equal to 0 the ridge penalty.
s	(Only used by q_glmnet) Value(s) of the penalty parameter lambda at which predictions are required, see glmnet::predict.glmnet() .
num.trees	(Only used by q_rf) Number of trees.
mtry	(Only used by q_rf) Number of variables to possibly split at in each node.
cv_args	(Only used by q_rf) Cross-validation parameters. Only used if multiple hyperparameters are given. K is the number of folds and rep is the number of replications.
SL.library	(Only used by q_s1) Either a character vector of prediction algorithms or a list containing character vectors, see SuperLearner::SuperLearner .

<code>env</code>	(Only used by <code>q_s1</code>) Environment containing the learner functions. Defaults to the calling environment.
<code>onlySL</code>	(Only used by <code>q_s1</code>) Logical. If TRUE, only saves and computes predictions for algorithms with non-zero coefficients in the super learner object.
<code>discreteSL</code>	(Only used by <code>q_s1</code>) If TRUE, select the model with the lowest cross-validated risk.
<code>objective</code>	(Only used by <code>q_xgboost</code>) specify the learning task and the corresponding learning objective, see xgboost::xgboost .
<code>params</code>	(Only used by <code>q_xgboost</code>) list of parameters.
<code>nrounds</code>	(Only used by <code>q_xgboost</code>) max number of boosting iterations.
<code>max_depth</code>	(Only used by <code>q_xgboost</code>) maximum depth of a tree.
<code>eta</code>	(Only used by <code>q_xgboost</code>) learning rate.
<code>nthread</code>	(Only used by <code>q_xgboost</code>) number of threads.

Details

`q_glm()` is a wrapper of [glm\(\)](#) (generalized linear model).

`q_glmnet()` is a wrapper of [glmnet::glmnet\(\)](#) (generalized linear model via penalized maximum likelihood).

`q_rf()` is a wrapper of [ranger::ranger\(\)](#) (random forest). When multiple hyper-parameters are given, the model with the lowest cross-validation error is selected.

`q_s1()` is a wrapper of [SuperLearner::SuperLearner](#) (ensemble model). `q_xgboost()` is a wrapper of [xgboost::xgboost](#).

Value

`q_model` object: function with arguments 'AH' (combined action and history matrix) and 'V_res' (residual value/expected utility).

See Also

[get_history_names\(\)](#), [get_q_functions\(\)](#).

Examples

```
library("polle")
### Single stage case
d1 <- sim_single_stage(5e2, seed=1)
pd1 <- policy_data(d1,
                    action="A",
                    covariates=list("Z", "B", "L"),
                    utility="U")
pd1

# available history variable names for the outcome regression:
get_history_names(pd1)

# evaluating the static policy a=1 using inverse
```

```

# propensity weighting based on the given Q-model:
pe1 <- policy_eval(type = "or",
                     policy_data = pd1,
                     policy = policy_def(1, name = "A=1"),
                     q_model = q_glm(formula = ~A*..))
pe1

# getting the fitted Q-function values
head(predict(get_q_functions(pe1), pd1))

#### Two stages:
d2 <- sim_two_stage(5e2, seed=1)
pd2 <- policy_data(d2,
                    action = c("A_1", "A_2"),
                    covariates = list(L = c("L_1", "L_2"),
                                      C = c("C_1", "C_2")),
                    utility = c("U_1", "U_2", "U_3"))
pd2

# available full history variable names at each stage:
get_history_names(pd2, stage = 1)
get_history_names(pd2, stage = 2)

# evaluating the static policy a=1 using outcome
# regression based on a glm model for each stage:
pe2 <- policy_eval(type = "or",
                     policy_data = pd2,
                     policy = policy_def(1, reuse = TRUE, name = "A=1"),
                     q_model = list(q_glm(~ A * L_1),
                                    q_glm(~ A * (L_1 + L_2))),
                     q_full_history = TRUE)
pe2

# getting the fitted Q-function values
head(predict(get_q_functions(pe2), pd2))

```

sim_multi_stage *Simulate Multi-Stage Data*

Description

Simulate Multi-Stage Data

Usage

```
sim_multi_stage(
  n,
  par = list(tau = 10, gamma = c(0, -0.2, 0.3), alpha = c(0, 0.5, 0.2, -0.5, 0.4), beta =
    c(3, -0.5, -0.5), psi = 1, xi = 0.3),
  a = function(t, x, beta, ...) {
```

```

prob <- lava::expit(beta[1] + (beta[2] * t^2) +
(beta[3] * x))
stats::rbinom(n = 1, size = 1, prob = prob)
},
seed = NULL
)

```

Arguments

- n** Number of observations.
- par** Named list with distributional parameters.
- **tau:** τ
 - **gamma:** γ
 - **alpha:** α
 - **beta:** β
 - **psi:** ψ
 - **xi:** ξ
- a** Function used to specify the action/treatment at every stage.
- seed** Integer.

Details

`sim_multi_stage` samples n iid observation O with the following distribution:

$$W \sim \mathcal{N}(0, 1) B \sim Ber(\xi)$$

For $k \geq 1$ let

$$(T_k - T_{k-1}) | X_{k-1}, A_{k-1}, W \sim \begin{cases} Exp\left\{ \exp(\gamma^T [1, X_{k-1}, W]) \right\} + \psi & A_{k-1} = 1 \\ \infty & A_{k-1} = 0 \end{cases} \quad X_k | T_k, X_{k-1}, B \sim \begin{cases} \mathcal{N}\{\alpha^T [1, T_k]\} & B = 1 \\ 0 & T_k = \infty \end{cases}$$

Note that ψ is the minimum increment.

Value

list with elements `stage_data` ([data.table::data.table](#)) and `baseline_data` ([data.table::data.table](#)).

<code>sim_single_stage</code>	<i>Simulate Single-Stage Data</i>
-------------------------------	-----------------------------------

Description

Simulate Single-Stage Data

Usage

```
sim_single_stage(
  n = 10000,
  par = c(k = 0.1, d = 0.5, a = 1, b = -2.5, c = 3, p = 0.3),
  action_model = function(Z, L, B, k, d) {
    k * (Z + L - 1) * Z^(-2) + d * (B == 1)

  },
  utility_model = function(Z, L, A, a, b, c) {
    Z + L + A * (c * Z + a * L + b)
  },
  seed = NULL,
  return_model = FALSE,
  ...
)
```

Arguments

<code>n</code>	Number of observations.
<code>par</code>	Named vector with distributional parameters. <ul style="list-style-type: none"> • <code>k</code>: κ • <code>d</code>: δ • <code>a</code>: α • <code>b</code>: β • <code>c</code>: γ • <code>p</code>: π
<code>action_model</code>	Function used to specify the action/treatment probability (logit link).
<code>utility_model</code>	Function used to specify the conditional mean utility.
<code>seed</code>	Integer.
<code>return_model</code>	If TRUE, the <code>lava::lvm</code> model is returned.
...	Additional arguments passed to <code>lava::lvm()</code> .

Details

`sim_single_stage` samples `n` iid observation $O = (B, Z, L, A, U)$ with the following distribution:

$$B \sim Bernoulli(\pi) \\ Z, L \sim Uniform([0, 1]) \\ A \mid Z, L, B \sim Bernoulli(expit\{\kappa Z^{-2}(Z+L-1)+\delta B\}U \mid Z, L, A \sim \mathcal{N}(Z+\delta B, \sigma^2))$$

Value

`data.frame` with `n` rows and columns `Z`, `L`, `B`, `A`, and `U`.

sim_single_stage_multi_actions
Simulate Single-Stage Multi-Action Data

Description

Simulate Single-Stage Multi-Action Data

Usage

```
sim_single_stage_multi_actions(n = 1000, seed = NULL)
```

Arguments

- | | |
|------|-------------------------|
| n | Number of observations. |
| seed | Integer. |

Details

`sim_single_stage_multi_actions` samples n iid observation $O = (z, x, a, u)$ with the following distribution:

$$z, x \sim Uniform([0, 1]) \tilde{a} \sim \mathcal{N}(0, 1) a \mid \tilde{a} \sim \begin{cases} 0 & \text{if } \tilde{a} < -1 \\ 1 & \text{if } \tilde{a} - 1 \leq a < 0.5 \\ 2 & \text{otherwise} \end{cases} \quad u \mid z, x \sim \mathcal{N}(x + z + I\{a = 2\}(x - 0.5) + I\{a = 1\}(x - 1), 0.1)$$

Value

data.frame with n rows and columns z, x, a, and u.

sim_two_stage *Simulate Two-Stage Data*

Description

Simulate Two-Stage Data

Usage

```
sim_two_stage(
  n = 10000,
  par = c(gamma = 0.5, beta = 1),
  seed = NULL,
  action_model_1 = function(C_1, beta, ...) stats::rbinom(n = NROW(C_1), size = 1, prob =
lava::expit(beta * C_1)),
```

```

action_model_2 = function(C_2, beta, ...) stats::rbinom(n = NROW(C_1), size = 1, prob =
  lava::expit(beta * C_2)),
deterministic_rewards = FALSE
)

```

Arguments

- n Number of observations.
- par Named vector with distributional parameters.
 - gamma: γ
 - beta: β
- seed Integer.
- action_model_1 Function used to specify the action/treatment at stage 1.
- action_model_2 Function used to specify the action/treatment at stage 2.
- deterministic_rewards Logical. If TRUE, the deterministic reward contributions are returned as well (columns U_1_A0, U_1_A1, U_2_A0, U_2_A1).

Details

`sim_two_stage` samples n iid observation O with the following distribution: BB is a random categorical variable with levels group1, group2, and group3. Furthermore,

$$B \sim \mathcal{N}(0, 1) L_1 \sim \mathcal{N}(0, 1) C_1 \mid L_1 \sim \mathcal{N}(L_1, 1) A_1 \mid C_1 \sim \text{Bernoulli}(\text{expit}(\beta C_1)) L_2 \sim \mathcal{N}(0, 1) C_2 \mid A_1, L_1 \sim \mathcal{N}(\gamma L_1 + \delta, 1) A_2 \sim \mathcal{N}(0, 1) L_3 \sim \mathcal{N}(0, 1)$$

The rewards are calculated as

$$U_1 = L_1 U_2 = A_1 \cdot C_1 + L_2 U_3 = A_2 \cdot C_2 + L_3.$$

Value

`data.table::data.table` with n rows and columns B, BB, L_1, C_1, A_1, L_2, C_2, A_2, L_3, U_1, U_2, U_3, (U_1_A0, U_1_A1, U_2_A0, U_2_A1).

`sim_two_stage_multi_actions`

Simulate Two-Stage Multi-Action Data

Description

Simulate Two-Stage Multi-Action Data

Usage

```
sim_two_stage_multi_actions(
  n = 1000,
  par = list(gamma = 0.5, beta = 1, prob = c(0.2, 0.4, 0.4)),
  seed = NULL,
  action_model_1 = function(C_1, beta, ...) stats::rbinom(n = NROW(C_1), size = 1, prob =
    lava::expit(beta * C_1))
)
```

Arguments

- n Number of observations.
- par Named vector with distributional parameters.
- gamma: γ
 - beta: β
 - prob: p
- seed Integer.
- action_model_1 Function used to specify the dichotomous action/treatment at stage 1.

Details

`sim_two_stage_multi_actions` samples n iid observation O with the following distribution: BB is a random categorical variable with levels `group1`, `group2`, and `group3`. Furthermore,

$$B \sim \mathcal{N}(0, 1) L_1 \sim \mathcal{N}(0, 1) C_1 \mid L_1 \sim \mathcal{N}(L_1, 1) P(A_1 = 'yes' \mid C_1) = \text{expit}(\beta C_1) P(A_1 = 'no' \mid C_1) = 1 - P(A_1 = 'yes')$$

The rewards are calculated as

$$U_1 = L_1 U_2 = A_1 \cdot C_1 + L_2 U_3 = A_2 \cdot C_2 + L_3.$$

Value

`data.table::data.table` with n rows and columns `B`, `BB`, `L_1`, `C_1`, `A_1`, `L_2`, `C_2`, `A_2`, `L_3`, `U_1`, `U_2`, `U_3`.

subset_id	<i>Subset Policy Data on ID</i>
-----------	---------------------------------

Description

`subset_id` returns a policy data object containing the given IDs.

Usage

```
subset_id(object, id, preserve_action_set = TRUE)
```

Arguments

- object Object of class [policy_data](#).
id character vectors of IDs.
preserve_action_set
 If TRUE, the action sets must be preserved.

Value

Object of class [policy_data](#).

Examples

```
library("polle")
### Single stage:
d <- sim_single_stage(5e2, seed=1)
# constructing policy_data object:
pd <- policy_data(d, action="A", covariates=list("Z", "B", "L"), utility="U")
pd

# getting the observation IDs:
get_id(pd)[1:10]

# subsetting on IDs:
pdsb <- subset_id(pd, id = 250:500)
pdsb
get_id(pdsb)[1:10]
```

Index

.policy_eval (policy_eval), 40
coef.policy_eval (policy_eval), 40
conditional, 3
control_blip, 4
control_blip(), 48
control_drql, 4
control_drql(), 48
control_earl, 5
control_earl(), 48
control_owl, 6
control_owl(), 48
control_ptl, 7
control_ptl(), 48
control_rwl, 8
control_rwl(), 48
copy_policy_data, 9
copy_policy_data(), 37

data.frame, 35
data.table::copy(), 9
data.table::data.table, 9, 11, 15, 19, 20,
 24, 28, 34, 35, 37–39, 44, 51, 56, 59,
 60
DTRlearn2::owl(), 6
DynTxRegime::earl(), 5
DynTxRegime::rwl(), 8

estimate.policy_eval (policy_eval), 40
fit_g_functions, 10
formula, 5, 8, 26, 49, 53
future.apply::future_apply(), 42, 49

g_empir (g_model), 25
g_empir(), 10, 41
g_glm (g_model), 25
g_glm(), 10, 41
g_glmnet (g_model), 25
g_model, 13, 25
g_rf (g_model), 25

g_rf(), 10, 41
g_sl (g_model), 25
g_sl(), 10, 41
g_xgboost (g_model), 25
get_action_set, 11
get_actions, 11
get_actions(), 37
get_g_functions, 12
get_g_functions(), 27, 45, 50
get_history (history), 28
get_history(), 37, 39
get_history_names, 13
get_history_names(), 26, 27, 37, 39, 53, 54
get_id, 14
get_id_stage, 15
get_K, 16
get_n, 16
get_policy, 17, 34
get_policy(), 45, 50
get_policy_actions, 18
get_policy_actions(), 45, 50
get_policy_functions
 (get_policy_functions.blip), 19
get_policy_functions(), 45, 50
get_policy_functions.blip, 19
get_policy_object, 21
get_q_functions, 22
get_q_functions(), 45, 50, 54
get_stage_action_sets, 23
get_utility, 24
get_utility(), 37
glm(), 26, 53, 54
glmnet::glmnet, 26, 53
glmnet::glmnet(), 26, 54
glmnet::predict.glmnet(), 26, 53

history, 14, 15, 28, 28

IC.policy_eval (policy_eval), 40

lava::estimate.default, 3, 45
lava::IC, 45
lava::lvm, 57
lava::lvm(), 57

merge.policy_eval (policy_eval), 40
modelObj::modelObj, 5, 8, 49

na.pass, 26, 53
nuisance_functions, 12, 22, 30, 41, 42

partial, 31
partial(), 37
plot(), 37
plot.policy_data, 32
plot.policy_eval, 33
plot.policy_eval(), 45
policy, 17, 32, 34, 38
policy_data, 9, 11, 12, 14–16, 23, 24, 28,
 30–32, 35, 36, 38, 39, 49, 61
policy_data(), 3, 10, 13, 41, 51
policy_def, 34, 38
policy_def(), 41
policy_eval, 12, 17, 18, 20–22, 33, 34, 40
policy_eval(), 3, 25, 35, 37, 50–52
policy_learn, 20, 34, 44, 47
policy_learn(), 25, 35, 37, 41, 51, 52
policy_object, 12, 17, 21, 22, 34, 49
policy_object (policy_learn), 47
policytree::hybrid_policy_tree(), 7, 48
policytree::policy_tree, 49
policytree::policy_tree(), 7
predict.nuisance_functions, 12, 22, 51
print.policy_data (policy_data), 35
print.policy_eval (policy_eval), 40
print.policy_learn (policy_learn), 47
print.policy_object (policy_learn), 47

q_glm(q_model), 52
q_glm(), 4, 42, 48
q_glmnet (q_model), 52
q_model, 13, 52
q_rf (q_model), 52
q_rf(), 4, 42, 48
q_sl (q_model), 52
q_sl(), 4, 42, 48
q_xgboost (q_model), 52

ranger::ranger, 26, 53
ranger::ranger(), 26, 54
scale(), 6
sim_multi_stage, 55
sim_single_stage, 56
sim_single_stage_multi_actions, 58
sim_two_stage, 58
sim_two_stage_multi_actions, 59
subset_id, 60
subset_id(), 37
summary.policy_data (policy_data), 35
summary.policy_eval (policy_eval), 40
SuperLearner::SuperLearner, 26, 53, 54

vcov.policy_eval (policy_eval), 40

xgboost::xgboost, 26, 54