

Package ‘precintcon’

October 14, 2022

Type Package

Title Precipitation Intensity, Concentration and Anomaly Analysis

Version 2.3.0

Date 2016-05-26

LazyData true

Author Lucas Venezian Povoa [aut, cre],
Jonas Teixeira Nery [ctb]

Maintainer Lucas Venezian Povoa <lucasvenez@gmail.com>

Description It contains functions to analyze the precipitation
intensity, concentration and anomaly.

URL <https://github.com/lucasvenez/precintcon>

BugReports <https://github.com/lucasvenez/precintcon/issues>

Depends R (>= 2.14), ggplot2 (>= 2.0.0), scales

License GPL (>= 2)

Collate 'app.r' 'as.precintcon.annual.r' 'as.annual.r'
'as.precintcon.daily.r' 'as.daily.r' 'as.precintcon.decade.r'
'as.decade.r' 'deciles.r' 'as.precintcon.deciles.r'
'precintcon.deciles.analysis.r' 'as.deciles.r'
'as.precintcon.fd.r' 'precintcon.fd.r' 'as.fd.r'
'as.precintcon.monthly.r' 'as.monthly.r'
'as.precintcon.seasonal.r' 'as.seasonal.r'
'precintcon.ci.per.year.analysis.r' 'ci.per.year.r'
'precintcon.ci.analysis.r' 'ci.r' 'cv.r' 'ff.index.r'
'precintcon.limits.analysis.r' 'limits.r' 'pcd.r'
'precintcon.pci.analysis.r' 'pci.r' 'pci.seasonal.r'
'pci.supraseasonal.r' 'pcp.r' 'precintcon.pn.analysis.r' 'pn.r'
'precintcon.plot.lorenz.r' 'pplot.ci.r'
'precintcon.plot.deciles.r' 'pplot.deciles.r'
'precintcon.plot.histogram.r' 'pplot.histogram.r'
'pplot.lorenz.r' 'pplot.pcd.r' 'precintcon.plot.pci.r'
'pplot.pci.r' 'pplot.pcp.r' 'precintcon.plot.pn.r' 'pplot.pn.r'
'precintcon.plot.rai.r' 'pplot.rai.r' 'precintcon.plot.spi.r'

```
'pplot.spi.r' 'precintcon.H.r' 'precintcon.Z.r'
'precintcon.b.r' 'precintcon.classification.r'
'precintcon.gamma.r' 'precintcon.ln.a.r' 'precintcon.max.r'
'precintcon.min.r' 'precintcon.monthly.aggregation.r'
'precintcon.plot.lorenz.ungrouped.r' 'precintcon.pn.r'
'precintcon.r' 'precintcon.r.squared.r'
'precintcon.rai.analysis.r' 'precintcon.read.data.r'
'precintcon.spi.analysis.r'
'precintcon.spi.per.year.analysis.r'
'precintcon.stat.analysis.r' 'rai.r' 'read.data.r'
'spi.per.year.r' 'spi.r' 'stat.r' 'tii.r' 'trend.test.r'
```

RoxygenNote 5.0.1

NeedsCompilation no

Repository CRAN

Date/Publication 2016-07-17 13:49:19

R topics documented:

app	3
as.annual	4
as.daily	5
as.decade	7
as.deciles	8
as.fd	9
as.monthly	10
as.seasonal	11
ci	12
ci.per.year	13
cv	14
daily	15
ff.index	16
limits	17
monthly	18
pcd	19
pci	20
pci.seasonal	21
pci.supraseasonal	22
pcp	23
pn	24
pplot.deciles	25
pplot.histogram	26
pplot.lorenz	27
pplot.pcd	28
pplot pci	30
pplot.pcp	31
pplot.pn	32

pplot.rai	33
pplot.spi	35
precintcon	36
rai	37
read.data	38
spi	39
spi.per.year	40
stat	41
tti	42
trend.test	43

app	<i>Amount and Percentage of Precipitation</i>
-----	---

Description

It calculates the amount and percentage of precipitation contributed by a such percent of rainiest days.

Usage

```
app(..., percent = 25)
```

Arguments

percent	is the percentage of the rainiest days to be considered (default = 25).
...	a set of daily precipitation series.

Value

data.frame containing the following variables:

- dataset is the dataset name of the precipitation serie;
- percentage is the percentage of the rainiest days;
- absolute is the absolute amount of precipitation generated by percentage
- relative is the percentage of precipitation benerated by percentage

Author(s)

Lucas Venezian Povoa <luCasVenez@gmail.com>

See Also

[read.data](#) [as.daily](#) [ci](#)

Examples

```
## 
# Loading the daily precipitation serie
data(daily)

## 
# Calculating amount and percentage of precipitation using different parameters

app(daily)

app(daily, percent = 20)

app(daily, percent = c(10, 15, 20, 25))
```

as.annual

Converting to seasonal precipitation serie.

Description

Converts a daily, monthly, or seasonal precipitation serie to an annual serie.

Usage

```
as.annual(object)
```

Arguments

object	a precintcon.daily, precintcon.monthly, or precintcon.seasonal object or a data.frame containing 33 or 3 columns.
--------	---

Value

A data.frame (precintcon.annual) containing the following variables:

- year is the year.
- precipitation is the precipitation amount in millimeters.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[as.daily](#) [as.monthly](#) [as.seasonal](#) [pplot.lorenz](#) [read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.annual(daily)
```

as.daily

Converting a data.frame to a daily precipitation serie

Description

Converts a data.frame to a precintcon.daily.

Usage

```
as.daily(object, na.value = NA)
```

Arguments

- | | |
|----------|--|
| object | a precintcon.daily or a data.frame containing 33 columns. |
| na.value | the value used for representing non-existent values (Default value: NA). |

Value

A data.frame (precintcon.daily) containing the following variables:

- year is the year.
- month is the month.
- d1 is the precipitation value in millimeters of the 1st day of the month.
- d2 is the precipitation value in millimeters of the 2nd day of the month.
- d3 is the precipitation value in millimeters of the 3rd day of the month.
- d4 is the precipitation value in millimeters of the 4th day of the month.
- d5 is the precipitation value in millimeters of the 5th day of the month.
- d6 is the precipitation value in millimeters of the 6th day of the month.
- d7 is the precipitation value in millimeters of the 7th day of the month.
- d8 is the precipitation value in millimeters of the 8th day of the month.
- d9 is the precipitation value in millimeters of the 9th day of the month.
- d10 is the precipitation value in millimeters of the 10th day of the month.
- d11 is the precipitation value in millimeters of the 11th day of the month.
- d12 is the precipitation value in millimeters of the 12th day of the month.

- d13 is the precipitation value in millimeters of the 13th day of the month.
- d14 is the precipitation value in millimeters of the 14th day of the month.
- d15 is the precipitation value in millimeters of the 15th day of the month.
- d16 is the precipitation value in millimeters of the 16th day of the month.
- d17 is the precipitation value in millimeters of the 17th day of the month.
- d18 is the precipitation value in millimeters of the 18th day of the month.
- d19 is the precipitation value in millimeters of the 19th day of the month.
- d20 is the precipitation value in millimeters of the 20th day of the month.
- d21 is the precipitation value in millimeters of the 21th day of the month.
- d22 is the precipitation value in millimeters of the 22th day of the month.
- d23 is the precipitation value in millimeters of the 23th day of the month.
- d24 is the precipitation value in millimeters of the 24th day of the month.
- d25 is the precipitation value in millimeters of the 25th day of the month.
- d26 is the precipitation value in millimeters of the 26th day of the month
- d27 is the precipitation value in millimeters of the 27th day of the month.
- d28 is the precipitation value in millimeters of the 28th day of the month.
- d29 is the precipitation value in millimeters of the 29th day of the month.
- d30 is the precipitation value in millimeters of the 30th day of the month.
- d31 is the precipitation value in millimeters of the 31th day of the month.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[as.decade](#) [as.annual](#) [as.seasonal](#) [as.monthly](#)

Examples

```
## 
# Loading the daily precipitation serie.
data(daily)

## 
# Converting precipitation
as.daily(daily)
```

as.decade*Converting a precipitation serie to a decade serie*

Description

It converts a daily, monthly or annual precipitation serie to a decade serie.

Usage

```
as.decade(object)
```

Arguments

object	a precintcon.daily, precintcon.monthly, precintcon.seasonal, precintcon.annual object or a data.frame containing 33 or 3 columns.
--------	---

Details

It excludes no complete decades for converting the serie, e.g., a serie starting in 1977 and finishing in 2008 will have the year 1977 to 1979 and 2000 to 2008 excluded, resulting into a serie of the years 1980 and 1990.

Value

A data.frame (precintcon.decade) containing the following variables:

- year is the year.
- precipitation is the decade's precipitation in millimeters.

Author(s)

Lucas Venezian Povoa <lcasvnez@gmail.com>

See Also

[as.precintcon.annual](#) [as.precintcon.seasonal](#) [as.precintcon.monthly](#) [as.precintcon.daily](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.decade(daily)
```

as.deciles	<i>Deciles of a precipitation serie</i>
------------	---

Description

Groups the monthly precipitation into deciles, i.e., it splits a precipitation serie into ten equal parts in crescent order, from the lower to the highest precipitation.

Usage

```
as.precintcon.deciles(object)
```

Arguments

object a daily or monthly precipitation serie.

Value

A data.frame (precintcon.deciles) containing the following variables:

- D1 corresponds to the precipitation values not exceeding 10% of the lowest values.
- D2 corresponds to the precipitation values not exceeding 20 of the lowest values.
- D3 corresponds to the precipitation values not exceeding 30 of the lowest values.
- D4 corresponds to the precipitation values not exceeding 40% of the lowest values.
- D5 is equals to the median that corresponds to the precipitation values not exceeding 50% of the lowest values.
- D6 corresponds to the precipitation values not exceeding 60% of the lowest values.
- D7 corresponds to the precipitation values not exceeding 70 of the lowest values.
- D8 corresponds to the precipitation values not exceeding 80 of the lowest values.
- D9 corresponds to the precipitation values not exceeding 90 of the lowest values.
- D10 corresponds to the precipitation values not exceeding 100 of the lowest values.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[read.data](#)

as.fd*Frequency distribution of a precipitation serie*

Description

Calculates the frequency distribution of a daily precipitation serie based on interval.

Usage

```
as.precintcon.fd(object, interval = 1)
```

Arguments

- | | |
|----------|---|
| object | a daily precipitation serie. |
| interval | the interval in millimeters for calculating the frequency distribution. |

Value

A data.frame (precintcon.fd) containing the following variables:

- `initial.class` is the initial value of the class.
- `final.class` is the final value of the class.
- `midpoint` is the middle point of the class.
- `n` is the absolute freqnecy, i.e., the number of days in each class.
- `sum.n` is the cumulative frequency, obtained by adding the absolute frequencies of all the classes up to the one under consideration.
- `P` is the pluviometric total of each class, obtained by multiplying `midpoint` by `n`.
- `sum.P` is the cummulative class's pluviometric total, obtained by adding the pluviometric total of all the classes up to the one under consideration.
- `p.sum.n` is the cumulative percentage of rainy days.
- `p.sum.P` is the cumulative percentage of rainfall amounts.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[read.data](#) [as.daily](#) [ci](#)

Examples

```
##  
# Loading the daily precipitation serie  
data(daily)  
  
##  
# Performing the frequency distribution  
as.precintcon.fd(daily)
```

as.monthly

Convert a daily precipitation serie to a monthly serie

Description

Converts a daily precipitation serie to a monthly serie.

Usage

```
as.monthly(object)
```

Arguments

object	a precintcon.daily object or a data.frame containing 33 or 3 columns
--------	--

Value

A data.frame (precintcon.monthly) containing the following variables:

- year is the year.
- month is the month.
- precipitation is the precipitation amount in millimeters.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[pplot.lorenz](#) [read.data](#)

Examples

```
## Loading the daily precipitation serie.  
#  
data(daily)  
  
## Converting precipitation  
#  
as.monthly(daily)
```

as.seasonal*Converting to seasonal precipitation serie*

Description

It converts a daily or monthly precipitation serie to a seasonal serie according to meteorological seasons.

Usage

```
as.seasonal(object)
```

Arguments

object	a precintcon.daily, or precintcon.monthly object or a data.frame containing 33 or 3 columns.
--------	--

Details

If the serie has no a month of a season, it is waived in conversion, e.g., if a serie has January and February of 1975, but no December of 1974, the first two months are removed of the resulting serie because the season that depends all of them is not complete.

Value

A data.frame (precintcon.seasonal) containing the following variables:

- year is the year.
- season is the season.
- precipitation is the precipitation amount in millimeters.

Author(s)

Lucas Venezian Povoa <luca.svenez@gmail.com>

See Also

[pplot.lorenz](#) [read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Converting precipitation  
as.seasonal(daily)
```

ci

Concentration Index

Description

Calculates the Concentration Index (CI) on a daily precipitation serie.

Usage

```
ci(..., interval = 1)
```

Arguments

interval	the interval in millimeters applied for calculating the concentration index. (Default value: 1)
...	a set of daily precipitation series.

Value

A data.frame containing the following variables:

- dataset is the precipitation serie name.
- a is the constant of the exponential curve defined via the least-squares method.
- b is the constant of the exponential curve defined via the least-squares method.
- r2 is the determination of coefficient of determination (R2) of the exponential model.
- A is the area over the exponential curve.
- S is the are compressed for the exponential curve.
- ci is the concentration index.

Author(s)

Lucas Venezian Povoa <lucausvenez@gmail.com>

See Also

[pplot.lorenz](#) [read.data.as.daily](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Performing the Concentration Index Analysis  
ci(daily, interval = 1)
```

ci.per.year	<i>Concentration Index per Year</i>
-------------	-------------------------------------

Description

Calculates the Concentration Index (CI) per year on a daily precipitation serie.

Usage

```
ci.per.year(object, interval = 1)
```

Arguments

- | | |
|----------|---|
| object | a daily precipitation serie. |
| interval | the interval in millimeters applied for calculating the concentration index. (Default value: 1) |

Value

A data.frame (precintcon.ci) containing the following variables:

- year is the year.
- ci is the concentration index.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[pplot.lorenz](#) [read.data.as.daily](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Performing the Concentration Index Analysis  
ci.per.year(daily, interval = 1)
```

cv

Coefficient of Variance

Description

It calculates the coefficient of variance of a monthly precipitation.

Usage

`cv(object)`

Arguments

`object` is a daily or monthly precipitation serie.

Details

A daily precipitation serie is transformed to a monthly serie.

Value

the coefficient of variance

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

Examples

```
##  
# Loading the montly precipitation serie.  
data(monthly)  
  
##  
# Calculating the Coefficient of Variance  
cv(monthly)
```

daily

Daily precipitation between 1976 and 2010

Description

This data set gives the daily precipitation (in millimeters) between 1976 and 2010, as compiled by the National Water Agency (ANA), Brazil.

Usage

```
data(daily)
```

Format

A data frame with 420 observations on the following 33 variables:

year the year.
month the month.
d1 the precipitation value in millimeters of the day #1 of the month.
d2 the precipitation value in millimeters of the day #2 of the month.
d3 the precipitation value in millimeters of the day #3 of the month.
d4 the precipitation value in millimeters of the day #4 of the month.
d5 the precipitation value in millimeters of the day #5 of the month.
d6 the precipitation value in millimeters of the day #6 of the month.
d7 the precipitation value in millimeters of the day #7 of the month.
d8 the precipitation value in millimeters of the day #8 of the month.
d9 the precipitation value in millimeters of the day #9 of the month.
d10 the precipitation value in millimeters of the day #10 of the month.
d11 the precipitation value in millimeters of the day #11 of the month.
d12 the precipitation value in millimeters of the day #12 of the month.
d13 the precipitation value in millimeters of the day #13 of the month.
d14 the precipitation value in millimeters of the day #14 of the month.
d15 the precipitation value in millimeters of the day #15 of the month.
d16 the precipitation value in millimeters of the day #16 of the month.
d17 the precipitation value in millimeters of the day #17 of the month.
d18 the precipitation value in millimeters of the day #18 of the month.
d19 the precipitation value in millimeters of the day #19 of the month.
d20 the precipitation value in millimeters of the day #20 of the month.
d21 the precipitation value in millimeters of the day #21 of the month.
d22 the precipitation value in millimeters of the day #22 of the month.

d23 the precipitation value in millimeters of the day #23 of the month.
d24 the precipitation value in millimeters of the day #24 of the month.
d25 the precipitation value in millimeters of the day #25 of the month.
d26 the precipitation value in millimeters of the day #26 of the month.
d27 the precipitation value in millimeters of the day #27 of the month.
d28 the precipitation value in millimeters of the day #28 of the month.
d29 the precipitation value in millimeters of the day #29 of the month.
d30 the precipitation value in millimeters of the day #30 of the month.
d31 the precipitation value in millimeters of the day #31 of the month.

Source

National Water Agency (ANA) <http://www2.ana.gov.br/Paginas/default.aspx>

Examples

```
data(daily)
## maybe pci(daily) ; rai(daily) ...
```

ff.index

F factor

Description

It calculates the Approximated Rainfall Erosivity Factor according to the ff index.

Usage

```
ff.index(object)
```

Arguments

object is a daily or monthly precipitation serie

Value

the ff index in millimeters

Author(s)

Lucas Venezian Povoa

References

Ferro, V., Giordano, G., Iovino, M. (1991). Isoerosivity and Erosion Risk Map for Sicily. Hydrolog. Sci. J. 36, 549-564

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Calculating ff index  
ff.index(daily)
```

limits

Limits

Description

Calculates the upper and lower limit on a set of daily or monthly precipitation series.

Usage

```
limits(...)
```

Arguments

... a set of daily or monthly precipitation series.

Value

A data.frame containing the following variables:

- dataset is the precipitation serie name.
- max is the maximum value in the precipitation serie.
- max.date is the first date of the maximum precipitation serie.
- min is the minimum value in the precipitation serie.
- min.date is the first date of the minimum precipitation serie.

Author(s)

Lucas Venezian Povoa <lcasvnez@gmail.com>

See Also

[read.data as.daily](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Concentration Index Analysis  
limits(monthly)
```

monthly

Monthly precipitation between 1950 and 1992.

Description

This dataset gives the monthly precipitation (in millimeters) between 1950 and 1992, as compiled by the National Water Agency (ANA), Brazil.

Usage

```
data(monthly)
```

Format

A data frame with 516 observations on the following 3 variables:

`year` the year.
`month` the month.
`precipitation` the precipitation amount in millimeters.

Source

National Water Agency (ANA) <http://www2.ana.gov.br/Paginas/default.aspx>

Examples

```
data(monthly)  
## maybe pci(monthly) ; rai(monthly) ...
```

pcd	<i>Precipitation Concentration Degree</i>
-----	---

Description

Calculates the Precipitation Concentration Degree (PCD) on a daily or monthly precipitation serie.

Usage

```
pcd(object)
```

Arguments

object a daily or monthly precipitation serie.

Value

A data.frame containing the following variables:

- year is the year.
- pcd is the percentage of precipitation concentration corresponding to a year. Values closer to 0 mean precipitation dispersion among all months and 1 concentration into only a month.

Author(s)

Lucas Venezian Povoa <lcasvenez@gmail.com>

References

Zhang LJ, Qian YF (2003) Annual distribution features of precipitation in China and their interannual variations. J Acta Meteorological Sinica 17:146-163

See Also

[pplot.pcd](#) [read.data](#) [as.daily](#) [as.monthly](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Precipitation Concentration Index analysis  
pcd(monthly)
```

pci*Precipitation Concentration Index*

Description

It calculates the Precipitation Concentration Index (PCI) on a daily or monthly precipitation serie.

Usage

```
pci(object)
```

Arguments

object a daily or monthly precipitation serie.

Value

A data.frame containing the following variables:

- **year** is the year.
- **pci** is the precipitation concentration index.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[pplot.pci](#) [read.data](#) [as.daily](#) [as.monthly](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Precipitation Concentration Index analysis  
pci(monthly)
```

pci.seasonal *Seasonal Precipitation Concentration Index*

Description

It calculates the Precipitation Concentration Index (PCI) in a seasonal granularity on a daily or monthly precipitation serie.

Usage

```
pci.seasonal(object, hemisthere)
```

Arguments

- | | |
|------------|---|
| object | is a daily or monthly precipitation serie |
| hemisthere | is the hemisthere, "n" for northern and "s" for south, of the precipitation serie |

Value

A data.frame containing the following variables:

- year is the year;
- season is the meteorological season; and
- pci.seasonal is the seasonal perception concentration index.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

Examples

```
##  
# Loading the daily precipitation serie  
data(daily)  
  
##  
# Calculating the seasonal perception concentration index  
pci.seasonal(daily, hemisthere = "s")
```

pci.supraseasonal *Supraseasonal Precipitation Concentration Index*

Description

It calculates the supraseasonal precipitation concentration index.

Usage

```
pci.supraseasonal(object, hemisthere = c("n", "s"))
```

Arguments

- object is a daily or monthly precipitation serie.
- hemisthere is the hemisthere, "n" for northern and "s" for south, of the precipitation serie.

Value

A data.frame containing the following variables:

- year is the year;
- season is the meteorological supraseason, wet or dry; and
- pci.season is the seasonal perception concentration index.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

References

M. de Luis, J. C. González-Hidalgo, M. Brunetti, L. A. Longares (2011). Precipitation concentration changes in Spain 1946–2005. *Natural Hazards and Earth System Science*, 5:11, pp. 1259–1265

Examples

```
##  
# Loading the daily precipitation serie  
data(daily)  
  
##  
# Calculating the supraseasonal precipitation concentration index  
pci.supraseasonal(daily, hemisthere = "s")
```

pcp

Precipitation Concentration Period

Description

Calculates the Precipitation Concentration Period (PCP) on a daily or monthly precipitation serie.

Usage

`pcp(object)`

Arguments

`object` a daily or monthly precipitation serie.

Value

A data.frame containing the following variables:

- `year` is the year.
- `pcp` is the precipitation concentration period, in degree, corresponding to a year. Results correspond to a month like below when using the ‘azimuth’ default values: 0 = January, 30 = February, 60 = March, . . . , 300 = November, and 330 = December.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

References

Zhang L.J., Qian Y.F. (2003) Annual distribution features of precipitation in China and their inter-annual variations. J Acta Meteorological Sinica 17:146-163

See Also

[pplot.pcp](#) [read.data](#) [as.daily](#) [as.monthly](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Precipitation Concentration Degree analysis  
pcd(monthly)
```

pn*Percentage of Normal*

Description

Calculates the Percentage of Normal (PN) on a daily or monthly precipitation serie.

Usage

```
pn(object, interval = 30, scale = "a")
```

Arguments

<code>object</code>	a daily or monthly precipitation serie.
<code>interval</code>	the number of months applied for calculating the percentage of normal.
<code>scale</code>	the scale used for calculating the percentage of normal, which should be either "w" for weak (not supported yet), "m" for month, "s" for season, or "d" for decades.

Value

A data.frame (`precintcon.pn`) containing the following variables:

- `year` is the year.
- `month` is the month. It exists only whether `scale = "m"`.
- `pn` is the percentage of normal.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[pplot.pn](#) [read.data](#) [as.daily](#) [as.monthly](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Percentage of Normal analysis  
pn(monthly)
```

pplot.deciles *Plot deciles*

Description

Plots the deciles of a precipitation serie.

Usage

```
pplot.deciles(..., ylab = "Precipitation",
  legend.title = "Legend", legend = NULL,
  fontsize = 10, axis.text.color = "black",
  export = FALSE, export.name = "deciles_plot.png",
  width = 8.6, height = 7.5, units = "cm", grouped = FALSE)
```

Arguments

ylab	the text for the y axis. (Default value: "Precipitation")
legend.title	the text for the legend title. (Default value: "Legend")
legend	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
fontsize	the font size value in pt. (Default value: 10)
axis.text.color	the legend colors. (Default value: "black")
export	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
export.name	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "deciles_plot.png")
width	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6)
height	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5)
units	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
grouped	the logical value for defining whether the graphs should be plotted in group.
...	a set of daily or monthly precipitation serie.

Author(s)

Lucas Venezian Povoa <lucausvenez@gmail.com>

See Also

[deciles](#) [read.data](#)

Examples

```
## Loading the monthly precipitation serie.
#
#data(monthly)

## Performing the a set of statistical analysis
#
pplot.deciles(monthly)
```

pplot.histogram *Plot histogram*

Description

Plots the histogram of a precipitation serie.

Usage

```
pplot.histogram(..., density = FALSE, xlab = "Precipitation (mm)",
ylab = "Frequency", legend.title = "Legend",
legend = NULL, fontsize = 10, axis.text.color = "black",
export = FALSE, export.name = "histogram_plot.png",
width = 10, height = 10, units = "cm")
```

Arguments

<code>density</code>	the logical value for defining whether the graph should be plotted with bars or lines. (Default value: FALSE)
<code>xlab</code>	the text for the x axis. (Default value: "Precipitation (mm)")
<code>ylab</code>	the text for the y axis. (Default value: "Frequency")
<code>legend.title</code>	the text for the legend title. (Default value: "Legend")
<code>legend</code>	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
<code>fontsize</code>	the font size value in pt. (Default value: 10)
<code>axis.text.color</code>	the legend colors. (Default value: "black")
<code>export</code>	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
<code>export.name</code>	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "histogram_plot.png")
<code>width</code>	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 10)
<code>height</code>	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 10)
<code>units</code>	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
<code>...</code>	a set of daily or monthly precipitation series.

Author(s)

Lucas Venezian Povoa <luca...@gmail.com>

See Also

[read.data](#)

Examples

```
## 
# Loading the daily precipitation serie.
data(daily)

## 
# Performing the a set of statistical analysis
pplot.histogram(daily)
```

pplot.lorenz

Plot Lorenz's curve

Description

Plots the Lorenz's curve of a precipitation serie.

Usage

```
pplot.lorenz(..., interval = 1, grouped = FALSE,
xlab = expression(sum(n[i])), i==1), ylab = expression(sum(P[i])), i==1),
legend.title = "Legend", legend = NULL, fontsize = 10,
axis.text.color = "black", export = FALSE, export.name = "lorenz_plot.png",
width = 8.6, height = 7.5, units = "cm")
```

Arguments

interval	the interval in millimeters applied for calculating the Lorenz's curve. (Default value: 1)
grouped	the logical value for defining whether all series should be plotted in the same graph or not. (Default value: FALSE)
xlab	the text for the x axis. (Default value: expression(sum(n[i]), i==1))
ylab	the text for the y axis. (Default value: expression(sum(P[i]), i==1))
legend.title	the text for the legend title. (Default value: "Legend")
legend	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
fontsize	the font size value in pt. (Default value: 10)
axis.text.color	the legend colors. (Default value: "black")

<code>export</code>	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
<code>export.name</code>	the text for defining the exported file name. It is only used if <code>export = TRUE</code> . (Default value: "histogram_plot.png")
<code>width</code>	the number for defining the exported graph width. It is only used if <code>export = TRUE</code> . (Default value: 10)
<code>height</code>	the number for defining the exported graph height. It is only used if <code>export = TRUE</code> . (Default value: 10)
<code>units</code>	the text for defining the units of the height and width parameters. It is only used if <code>export = TRUE</code> . (Default value: "cm")
...	a set of daily precipitation series.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[ci](#) [read.data](#) [as.daily](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Performing the a set of statistical analysis  
pplot.ci(daily, interval = 1)
```

Description

Plots the Precipitation Concentraition Degre per year of a precipitation serie.

Usage

```
pplot.pcd(..., xlab = "Year", ylab = "PCD",  
          ylim = c(0,360), legend = NULL, fontsize = 10, axis.text.color = "black",  
          export = FALSE, export.name = "pcd_plot.png", width = 8.6,  
          height = 7.5, units = "cm")
```

Arguments

xlab	the text for the x axis. (Default value: "Year")
ylab	the text for the y axis. (Default value: "PCD")
ylim	the limits of the y axis. (Default value: c(0, 360))
legend	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
fontsize	the font size value in pt. (Default value: 10)
axis.text.color	the legend colors. (Default value: "black")
export	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
export.name	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "pcd_plot.png")
width	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6)
height	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5)
units	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
...	a set of daily or monthly precipitation series.

Author(s)

Lucas Venezian Povoa <lcasvenez@gmail.com>

References

Zhang LJ, Qian YF (2003) Annual distribution features of precipitation in China and their interannual variations. J Acta Meteorological Sinica 17:146-163

See Also

[pcd](#) [read.data](#)

Examples

```
## 
# Loading the daily precipitation serie.
data(daily)

## 
# Plotting PCD index per year
pplot.pcd(daily)
```

pplot.pci

Plot Precipitation Concentration Index

Description

Plots the Precipitation Concentration Index of a precipitation serie.

Usage

```
pplot.pci(..., xlab = "Years", ylab = "PCI", legend = NULL,  
          fontsize = 10, axis.text.color = "black", export = FALSE,  
          export.name = "pci_plot.png", width = 10, height = 10, units = "cm")
```

Arguments

<code>xlab</code>	the text for the x axis. (Default value: "Years")
<code>ylab</code>	the text for the y axis. (Default value: "PCI")
<code>legend</code>	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
<code>fontsize</code>	the font size value in pt. (Default value: 10)
<code>axis.text.color</code>	the legend colors. (Default value: "black")
<code>export</code>	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
<code>export.name</code>	the text for defining the exported file name. It is only used if <code>export = TRUE</code> . (Default value: "pci_plot.png")
<code>width</code>	the number for defining the exported graph width. It is only used if <code>export = TRUE</code> . (Default value: 10)
<code>height</code>	the number for defining the exported graph height. It is only used if <code>export = TRUE</code> . (Default value: 10)
<code>units</code>	the text for defining the units of the height and width parameters. It is only used if <code>export = TRUE</code> . (Default value: "cm")
<code>...</code>	a set of daily precipitation series.

Author(s)

Lucas Venezian Povoa <luca.svenez@gmail.com>

See Also

[read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Performing the a set of statistical analysis  
pplot.pci(daily)
```

pplot.pcp

Plot Precipitation Concentration Period per Year

Description

Plots the Precipitation Concentration Period per year of a precipitation serie.

Usage

```
pplot.pcp(..., xlab = "Year",  
          ylab = "PCP", ylim = c(0,360), legend = NULL, fontsize = 10,  
          axis.text.color = "black", export = FALSE, export.name = "pcd_plot.png",  
          width = 8.6, height = 7.5, units = "cm")
```

Arguments

xlab	the text for the x axis. (Default value: "Year")
ylab	the text for the y axis. (Default value: "PCD")
ylim	the limits of the y axis. (Default value: c(0, 360))
legend	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
fontsize	the font size value in pt. (Default value: 10)
axis.text.color	the legend colors. (Default value: "black")
export	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
export.name	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "pcd_plot.png")
width	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6)
height	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5)
units	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
...	a set of daily or monthly precipitation series.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

References

Zhang LJ, Qian YF (2003) Annual distribution features of precipitation in China and their interannual variations. J Acta Meteorological Sinica 17:146-163

See Also

[pcp](#) [read.data](#)

Examples

```
## 
# Loading the daily precipitation serie.
data(daily)

## 
# Plotting PCP per year
pplot.pcp(daily)
```

pplot.pn

Plot Percent of Normal

Description

Plots the Percent of Normal of a precipitation serie.

Usage

```
pplot.pn(..., interval = 30, scale = "a", xlab = NA, ylab = "PN",
          fontsize = 10, axis.text.color = "black", legend = NULL,
          export = FALSE, export.name = "pn_plot.png", width = 10,
          height = 10, units = "cm")
```

Arguments

<code>interval</code>	the number of months applied for calculating the percentage of normal.
<code>scale</code>	the scale used for calculating the percentage of normal, which should be either "w" for weak (not supported yet), "m" for month, "s" for season, or "d" for decades.
<code>xlab</code>	the text for the x axis. (Default value: NA)
<code>ylab</code>	the text for the y axis. (Default value: "PN")
<code>fontsize</code>	the font size value in pt. (Default value: 10)
<code>axis.text.color</code>	the legend colors. (Default value: "black")

legend	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
export	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
export.name	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "pci_plot.png")
width	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 10)
height	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 10)
units	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
...	a set of daily or monthly precipitation serie.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[read.data](#)

Examples

```
## 
# Loading the daily precipitation serie.
data(daily)

## 
# Performing the a set of statistical analysis
pplot.pn(daily)
```

Description

Plots the Rainfall Anomaly Index of a precipitation serie.

Usage

```
pplot.rai(..., granularity = "m", xlab = "Month", ylab = "RAI",
      ylim = c(-3,3), legend = NULL, fontsize = 10,
      axis.text.color = "black", export = FALSE,
      export.name = "rai_plot.png", width = 8.6,
      height = 7.5, units = "cm")
```

Arguments

<code>granularity</code>	the granularity applied for calculating the rainfall anomaly index, which should be either "a" for annual granularity or "m" for monthly granularity ". (Default value: "m")
<code>xlab</code>	the text for the x axis. (Default value: "Month")
<code>ylab</code>	the text for the y axis. (Default value: "RAI")
<code>ylim</code>	the limits of the y axis. (Default value: c(-3, 3))
<code>legend</code>	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
<code>fontsize</code>	the font size value in pt. (Default value: 10)
<code>axis.text.color</code>	the legend colors. (Default value: "black")
<code>export</code>	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
<code>export.name</code>	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "rai_plot.png")
<code>width</code>	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6)
<code>height</code>	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5)
<code>units</code>	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
<code>...</code>	a set of daily or monthly precipitation series.

Author(s)

Lucas Venezian Povoa <lucausvenez@gmail.com>

References

Rooy, M. P. van. A Rainfall anomaly index independent of time and space, Notos. v.14, p.43-48, 1965.

See Also

[read.data](#)

Examples

```
## 
# Loading the daily precipitation serie.
data(daily)

## 
# Performing the a set of statistical analysis
pplot.rai(daily, granularity = "m")
```

pplot.spi*Plot Standardized Precipitation Index*

Description

Plots the Standardized Precipitation Index of a precipitation serie.

Usage

```
pplot.spi(..., period = 3, distribution = "Gamma", xlab = "Months",
ylab = "SPI", ylim = c(-3,3), legend = NULL, fontsize = 10,
axis.text.color = "black", export = FALSE, export.name = "spi_plot.png",
width = 8.6, height = 7.5, units = "cm")
```

Arguments

period	the number of months to be aggregated for calculating the standardized precipitation index. (Default value: 3)
distribution	it has no effect yet. (Default value: "Gamma")
xlab	the text for the x axis. (Default value: "Months")
ylab	the text for the y axis. (Default value: "SPI")
ylim	the limits of the y axis. (Default value: c(-3, 3))
legend	the text vector for the legend items. If NULL the legends will be equals to the variable names. (Default value: NULL)
fontsize	the font size value in pt. (Default value: 10)
axis.text.color	the legend colors. (Default value: "black")
export	the logical value for defining whether the graph should be export to a file or not. (Default value: FALSE)
export.name	the text for defining the exported file name. It is only used if export = TRUE. (Default value: "spi_plot.png")
width	the number for defining the exported graph width. It is only used if export = TRUE. (Default value: 8.6)
height	the number for defining the exported graph height. It is only used if export = TRUE. (Default value: 7.5)
units	the text for defining the units of the height and width parameters. It is only used if export = TRUE. (Default value: "cm")
...	a set of daily or monthly precipitation series.

Author(s)

Lucas Venezian Povoa <luca\$venez@gmail.com>

See Also

[read.data](#)

Examples

```
##  
# Loading the daily precipitation serie.  
data(daily)  
  
##  
# Performing the a set of statistical analysis  
pplot.spi(daily)
```

Description

It contains functions to analyze the precipitation intensity, concentration and anomaly.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>
Jonas Teixeira Nery <jonas@ourinhos.unesp.br>

References

- Michael J. Hayes (2015). *Comparison of Major Drought Indices*. National Drought Mitigation Center. <http://goo.gl/skHfs9>.
- Gibbs, W. J. (1967). *Rainfall deciles as drought indicators*. Bureau of Meteorology Bulletin, n. 48. Commonwealth of Australia.
- Luis, M. D., Gonzalez-Hidalgo, J. C., Brunetti, M., Longares, L. A. (2011). *Precipitation concentration changes in Spain 1946-2005*. Natural Hazards and Earth System Science, v. 11, n. 5, p. 1259–1265.
- Martin-Vide, J. (2004). *Spatial distribution of a daily precipitation concentration index in peninsular Spain*. International Journal of Climatology, v. 24, n. 8, p. 959–971.
- Guttman, N. B. (1999). *Accepting the standardized precipitation index: a calculation algorithm*. Journal of the American Water Resources Association, v. 35, n. 2, p. 311–322. Blackwell Publishing Ltd.
- Balling, R., Hulme, M. (1991). *Filters and approximate confidence intervals for interpreting rainfall anomaly indices*. Journal of Climate, v. 4, n. 8, p. 837–847.

rai	<i>Rainfall Anomaly Index</i>
-----	-------------------------------

Description

Calculates the Rainfall Anomaly Index (RAI) on a daily or monthly precipitation serie.

Usage

```
rai(object, granularity = "m")
```

Arguments

object	a daily or monthly precipitation serie.
granularity	the granularity applied for calculating the rainfall anomaly index, which should be either "m" for monthly granularity or "a" for annual granularity. (Default value: "m")

Value

A data.frame (precintcon.rai) containing the following variables:

- year is the year.
- month is the month. This attribute exists only when granularity = "m".
- rai is the rainfall anomaly index.

Author(s)

Lucas Venezian Povoa <lucausvenez@gmail.com>

References

Van Rooy, M. P. "A rainfall anomaly index independent of time and space." Notos 14.43 (1965): 6.

See Also

[pplot.rai](#) [read.data](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Rainfall Anomaly Index analysis  
rai(monthly, granularity = "m")
```

read.data*Load a precipitation series***Description**

Load a file with a daily or monthly precipitation series.

Usage

```
read.data(file, sep = ",", dec = ".", header = TRUE, na.value = NA)
```

Arguments

<code>file</code>	a string containing the file path.
<code>sep</code>	the character applied for delimited columns. (Default value: ",")
<code>dec</code>	the character applied for defined decimal point. (Default value: ".")
<code>header</code>	a logical value defining whether the first line of the file refers to column names. (Default value: TRUE)
<code>na.value</code>	the value used for representing missing values. (Default value: NA)

Value

A data frame containing a representation of the data in the file. The file is addressed as precintcon.daily or precintcon.monthly depending of its structure.

The file should contains three columns when loading monthly series and thirty three columns when loading daily series.

The first columns refers to years and the second one refers to months. When dealing with daily datasets, the thirty one remaining columns refers to the amount of precipitation in the days of the months. Otherwise, the remaining column refers to the amount of precipitation in each month.

Author(s)

Lucas Venezian Povoa <lucausvenez@gmail.com>

See Also

[daily](#) [monthly](#) [read.table](#) [read.csv](#) [read.csv2](#)

Examples

```
##  
# Loading a serie on Windows  
## Not run: d1 <- read.data("C:\\PRECINTCON\\203040.csv", sep = ";", dec = ".", header = TRUE)  
  
##  
# Loading a serie on Unix-like  
## Not run: d1 <- read.data("/home/precintcon/203040.csv", sep = ";", dec = ".", header = TRUE)
```

spi	<i>Standardized Precipitation Index</i>
-----	---

Description

Calculates the Standardized Precipitation Index (SPI) on a daily or monthly precipitation serie.

Usage

```
spi(object, period = 3, distribution = "Gamma")
```

Arguments

- | | |
|--------------|--|
| object | a daily or monthly precipitation serie. |
| period | the number of months to be aggregated in the calculation of the standardized precipitation index. (Default value: 3) |
| distribution | it has no effect yet. (Default value: "Gamma") |

Value

A data.frame (precintcon.spi) containing the following variables:

- year is the year.
- month is the month.
- spi is the standardized precipitation index.

Author(s)

Lucas Venezian Povoa <lucasvenez@gmail.com>

See Also

[precintcon.plot.spi](#) [read.data](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Standardized Precipitation Index  
spi(monthly, period = 3)
```

spi.per.year*Standardized Precipitation Index***Description**

Calculates the Standardized Precipitation Index (SPI) per year on a daily or monthly precipitation serie.

Usage

```
spi.per.year(object, period = 3, distribution = "Gamma", FUN = mean)
```

Arguments

- | | |
|---------------------|---|
| object | a daily or monthly precipitation serie. |
| period | the number of months to be aggregate in the calculation of the standardized precipitation index. (Default value: 3) |
| distribution | (it has no effect yet). |
| FUN | the function used to summarize the standardized precipitation index per year. (Default function: mean). |

Value

A data.frame (precintcon.spi.per.year) containing the following variables:

- **year** is the year.
- **spi** is the standardized precipitation index.

Author(s)

Lucas Venezian Povoa <lcasvenez@gmail.com>

See Also

[spi.read.data](#)

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Performing the Standardized Precipitation Index  
spi.per.year(monthly, period = 3)
```

stat*Basic statistics for precipitation datasets.*

Description

Perform the calculation of basic statistics of precipitation datasets.

Usage

```
stat(...)
```

Arguments

... a set of daily or monthly precipitation serie.

Value

A data.frame (precintcon.stat) containing the following variables:

- dataset is the precipitation serie name.
- mean.daily is the daily average precipitation. It exists only for daily datasets.
- sd.daily is the standard deviation of a daily precipitation serie. It exists only for daily datasets.
- var.daily is the variance of a daily precipitation serie. It exists only for daily datasets.
- mean.monthly is the monthly average precipitation.
- sd.monthly is the standard deviation of a monthly precipitation serie.
- var.monthly is the variance of a monthly precipitation serie.
- total is the total precipitation.

Author(s)

Lucas Venezian Povoa <lucaсvenez@gmail.com>

Examples

```
##  
# Loading the monthly precipitation serie.  
data(monthly)  
  
##  
# Plotting the deciles.  
stat(monthly)
```

tti	<i>Temporaly Irregularity Index</i>
------------	-------------------------------------

Description

It calculates the temporaly irregularity index according to the function $\text{sum}(\log(P_{i+1}/P_i))/(n-1)$, where P_i is the precipitation amount of year i , and n is the number of years.

Usage

```
tti(object)
```

Arguments

object is a daily or monthly precipitation serie

Details

Daily or monthly precipitation series are transformed to annual series.

Value

the temporaly irregularity index according to the function $\text{sum}(\log(P_{i+1}/P_i))/(n-1)$

Author(s)

Lucas Venezian Povoa

Examples

```
##  
# Loading the monthly precipitation serie  
data(monthly)  
  
##  
# Calculationg the Temporaly Irregularity Index  
tti(monthly)
```

trend.test	<i>Mann-Kendall Trend Test</i>
------------	--------------------------------

Description

It calculates a trend test using the rank-based nonparametric Mann-Kendall method.

Usage

```
trend.test(object, significance.level = 0.05)
```

Arguments

`object` is a daily or monthly precipitation serie.

`significance.level` is the significance level to be considered in the analysis. It is usually equals to 5% (default: 0.05).

Value

A trend test index.

Author(s)

Lucas Venezian Povoa <lucausvenez@gmail.com>

References

H. B. Mann (1945). Nonparametric tests against trend. *Econometrica*, vol. 13, pp. 245-259. M. G. Kendall (1975). *Rank Correlation Methods*. Griffin, London, UK.

See Also

[ci](#) [ci.per.year](#) [pci](#) [read.data](#)

Index

- * **(PCP)**
 - pplot.pcp, 31
- * **PCD**
 - pcd, 19
 - pcp, 23
 - pplot.pcd, 28
- * **annual**
 - as.annual, 4
- * **anomaly**
 - pplot.rai, 33
 - precintcon, 36
 - rai, 37
 - spi, 39
 - spi.per.year, 40
- * **concentration**
 - ci, 12
 - ci.per.year, 13
 - pcd, 19
 - pci, 20
 - pcp, 23
 - pplot.pcd, 28
 - pplot pci, 30
 - pplot.pcp, 31
 - precintcon, 36
- * **curve**
 - pplot.lorenz, 27
- * **daily**
 - as.daily, 5
- * **datasets**
 - daily, 15
 - monthly, 18
- * **data**
 - read.data, 38
- * **decade**
 - as.decade, 7
- * **deciles**
 - as.deciles, 8
 - pplot.deciles, 25
- * **degree**
- pcd, 19
- pcp, 23
- pplot.pcd, 28
- * **distribution**
 - as.fd, 9
- * **file**
 - read.data, 38
- * **frequency**
 - as.fd, 9
- * **histogram**
 - pplot.histogram, 26
- * **import**
 - read.data, 38
- * **index**
 - ci, 12
 - ci.per.year, 13
 - pci, 20
 - pplot pci, 30
 - pplot.spi, 35
 - rai, 37
 - spi, 39
 - spi.per.year, 40
- * **intensity**
 - precintcon, 36
- * **limits**
 - limits, 17
- * **lorenz's**
 - pplot.lorenz, 27
- * **monthly**
 - as.monthly, 10
- * **normal**
 - pn, 24
 - pplot.pn, 32
- * **of**
 - pn, 24
 - pplot.pn, 32
- * **package**
 - precintcon, 36
- * **percent**

pn, 24
pplot.pn, 32
*** period**
 pplot.pcp, 31
*** precintcon**
 as.deciles, 8
*** precipitation**
 as.annual, 4
 as.daily, 5
 as.decade, 7
 as.fd, 9
 as.monthly, 10
 as.seasonal, 11
 ci, 12
 ci.per.year, 13
 limits, 17
 pcd, 19
 pci, 20
 pcp, 23
 pn, 24
 pplot.deciles, 25
 pplot.histogram, 26
 pplot.lorenz, 27
 pplot.pcd, 28
 pplot.pci, 30
 pplot.pcp, 31
 pplot.pn, 32
 pplot.rai, 33
 pplot.spi, 35
 precintcon, 36
 rai, 37
 read.data, 38
 spi, 39
 spi.per.year, 40
 stat, 41
 trend.test, 43
*** rainfall**
 pplot.rai, 33
 precintcon, 36
 rai, 37
 spi, 39
 spi.per.year, 40
*** read**
 read.data, 38
*** seasonal**
 as.seasonal, 11
*** standardized**
 pplot.spi, 35
 *** summary**
 stat, 41
 *** table**
 read.data, 38
 *** test**
 trend.test, 43
 *** trend**
 trend.test, 43
 app, 3
 as.annual, 4, 6
 as.daily, 3, 4, 5, 9, 12, 13, 17, 19, 20, 23, 24,
 28
 as.decade, 6, 7
 as.deciles, 8
 as.fd, 9
 as.monthly, 4, 6, 10, 19, 20, 23, 24
 as.precintcon.annual, 7
 as.precintcon.annual(as.annual), 4
 as.precintcon.daily, 7
 as.precintcon.daily(as.daily), 5
 as.precintcon.decade(as.decade), 7
 as.precintcon.deciles(as.deciles), 8
 as.precintcon.fd(as.fd), 9
 as.precintcon.monthly, 7
 as.precintcon.monthly(as.monthly), 10
 as.precintcon.seasonal, 7
 as.precintcon.seasonal(as.seasonal), 11
 as.seasonal, 4, 6, 11
 ci, 3, 9, 12, 28, 43
 ci.per.year, 13, 43
 cv, 14
 daily, 15, 38
 deciles, 25
 deciles(as.deciles), 8
 ff.index, 16
 limits, 17
 monthly, 18, 38
 pcd, 19, 29
 pci, 20, 43
 pci.seasonal, 21
 pci.supraseasonal, 22
 pcp, 23, 32
 pn, 24

pplot.ci (pplot.lorenz), 27
 pplot.deciles, 25
 pplot.histogram, 26
 pplot.lorenz, 4, 10–13, 27
 pplot.pcd, 19, 28
 pplot.pci, 20, 30
 pplot.pcp, 23, 31
 pplot.bn, 24, 32
 pplot.rai, 33, 37
 pplot.spi, 35
 precintcon, 36
 precintcon-package (precintcon), 36
 precintcon.ci.analysis (ci), 12
 precintcon.ci.per.year.analysis
 (ci.per.year), 13
 precintcon.deciles.analysis
 (as.deciles), 8
 precintcon.fd (as.fd), 9
 precintcon.limits.analysis (limits), 17
 precintcon.pci.analysis (pci), 20
 precintcon.plot.deciles
 (pplot.deciles), 25
 precintcon.plot.histogram
 (pplot.histogram), 26
 precintcon.plot.lorenz (pplot.lorenz),
 27
 precintcon.plot.pci (pplot.pci), 30
 precintcon.plot.bn (pplot.bn), 32
 precintcon.plot.rai (pplot.rai), 33
 precintcon.plot.spi, 39
 precintcon.plot.spi (pplot.spi), 35
 precintcon.bn.analysis (bn), 24
 precintcon.rai.analysis (rai), 37
 precintcon.read.data (read.data), 38
 precintcon.spi.analysis (spi), 39
 precintcon.spi.per.year.analysis
 (spi.per.year), 40
 precintcon.stat.analysis (stat), 41

 rai, 37
 read.csv, 38
 read.csv2, 38
 read.data, 3, 4, 8–13, 17, 19, 20, 23–25,
 27–30, 32–34, 36, 37, 38, 39, 40, 43
 read.table, 38

 spi, 39, 40
 spi.per.year, 40
 stat, 41